

1-1-2015

## An Extended TOPSIS Method for Multiple Attribute Decision Making based on Interval Neutrosophic Uncertain Linguistic Variables

Said Broumi

Jun Ye

Florentin Smarandache

Follow this and additional works at: [https://digitalrepository.unm.edu/nss\\_journal](https://digitalrepository.unm.edu/nss_journal)

---

### Recommended Citation

Broumi, Said; Jun Ye; and Florentin Smarandache. "An Extended TOPSIS Method for Multiple Attribute Decision Making based on Interval Neutrosophic Uncertain Linguistic Variables." *Neutrosophic Sets and Systems* 8, 1 (2019). [https://digitalrepository.unm.edu/nss\\_journal/vol8/iss1/5](https://digitalrepository.unm.edu/nss_journal/vol8/iss1/5)

This Article is brought to you for free and open access by UNM Digital Repository. It has been accepted for inclusion in *Neutrosophic Sets and Systems* by an authorized editor of UNM Digital Repository. For more information, please contact [amywinter@unm.edu](mailto:amywinter@unm.edu).



# An Extended TOPSIS Method for Multiple Attribute Decision Making based on Interval Neutrosophic Uncertain Linguistic Variables

<sup>1</sup>Said Broumi, <sup>2</sup>Jun Ye, <sup>3</sup>Florentin Smarandache

<sup>1</sup>Faculty of Lettres and Humanities, Hay El Baraka Ben M'sik Casablanca B.P. 7951, University of Hassan II Casablanca, Morocco, broumisaid78@gmail.com

<sup>2</sup>Department of Electrical and Information Engineering, Shaoxing University, No. 508 Huancheng West Road, Shaoxing, Zhejiang Province 312000, P.R. China  
yehjun@aliyun.com

<sup>3</sup>Department of Mathematics, University of New Mexico, 705 Gurley Avenue, Gallup, NM 87301, USA  
fsmarandache@gmail.com

**Abstract:** The interval neutrosophic uncertain linguistic variables can easily express the indeterminate and inconsistent information in real world, and TOPSIS is a very effective decision making method more and more extensive applications. In this paper, we will extend the TOPSIS method to deal with the interval neutrosophic uncertain linguistic information, and propose an extended TOPSIS method to solve the multiple attribute decision making problems in which the attribute value takes the form of the interval neutrosophic uncertain linguistic variables

and attribute weight is unknown. Firstly, the operational rules and properties for the interval neutrosophic variables are introduced. Then the distance between two interval neutrosophic uncertain linguistic variables is proposed and the attribute weight is calculated by the maximizing deviation method, and the closeness coefficients to the ideal solution for each alternatives. Finally, an illustrative example is given to illustrate the decision making steps and the effectiveness of the proposed method.

**Keywords:** The interval neutrosophic linguistic, multiple attribute decision making, TOPSIS, maximizing deviation method

## I-Introduction

F. Smarandache [7] proposed the neutrosophic set (NS) by adding an independent indeterminacy-membership function. The concept of neutrosophic set is generalization of classic set, fuzzy set [25], intuitionistic fuzzy set [22], interval intuitionistic fuzzy set [23,24] and so on. In NS, the indeterminacy is quantified explicitly and truth-membership, indeterminacy membership, and false-membership are completely independent. From scientific or engineering point of view, the neutrosophic set and set-theoretic view, operators need to be specified. Otherwise, it will be difficult to apply in the real applications. Therefore, H. Wang et al [8] defined a single valued neutrosophic set

(SVNS) and then provided the set theoretic operations and various properties of single valued neutrosophic sets. Furthermore, H. Wang et al.[9] proposed the set theoretic operations on an instance of neutrosophic set called interval valued neutrosophic set (IVNS) which is more flexible and practical than NS. The works on neutrosophic set (NS) and interval valued neutrosophic set (IVNS), in theories and application have been progressing rapidly (e.g., [1,2,4,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,27,28,29,30,31,32,33,35,36,37,38,39,40,41,42,43,44,45,46,47,48,53].

Multiple attribute decision making (MADM) problem are of importance in most kinds of fields such as engineering,

economics, and management. In many situations decision makers have incomplete, indeterminate and inconsistent information about alternatives with respect to attributes. It is well known that the conventional and fuzzy or intuitionistic fuzzy decision making analysis [26, 50, 51.] using different techniques tools have been found to be inadequate to handle indeterminate and inconsistent data. So, Recently, neutrosophic multicriteria decision making problems have been proposed to deal with such situation.

TOPSIS (Technique for Order Performance by Similarity to Ideal Solution) method, initially introduced by C. L. Hwang and Yoon [3], is a widely used method for dealing with MADM problems, which focuses on choosing the alternative with the shortest distance from the positive ideal solution (PIS) and the farthest distance from the negative ideal solution (NIS). The traditional TOPSIS is only used to solve the decision making problems with crisp numbers, and many extended TOPSIS were proposed to deal with fuzzy information. Z. Yue [55] extended TOPSIS to deal with interval numbers, G. Lee et al.[5] extend TOPSIS to deal with fuzzy numbers, P. D. Liu and Su [34], Y. Q. Wei and Liu [49] extended TOPSIS to linguistic information environments, Recently, Z. Zhang and C. Wu [53] proposed the single valued neutrosophic or interval neutrosophic TOPSIS method to calculate the relative closeness coefficient of each alternative to the single valued neutrosophic or interval neutrosophic positive ideal solution, based on which the considered alternatives are ranked and then the most desirable one is selected. P. Biswas et al. [32] introduced single-valued neutrosophic multiple attribute decision making problem with incompletely known or completely unknown attribute weight information based on modified GRA.

Based on the linguistic variable and the concept of interval neutrosophic sets, J. Ye [19] defined interval neutrosophic linguistic variable, as well as its operation principles, and developed some new aggregation operators for the interval neutrosophic linguistic information, including interval neutrosophic linguistic arithmetic weighted average (INLAWA) operator, linguistic geometric weighted average (INLGWA) operator and discuss some properties. Furthermore, he proposed the decision making method for multiple attribute decision making (MADM) problems with an illustrated example to show the process of decision making and the effectiveness of the proposed method. In order to process incomplete, indeterminate and inconsistent information more efficiency and precisely J. Ye [20] further proposed the interval neutrosophic uncertain linguistic variables by combining uncertain linguistic variables and interval neutrosophic sets, and proposed the operational rules, score function, accuracy functions, and certainty function of interval neutrosophic uncertain linguistic variables. Then the interval neutrosophic

uncertain linguistic weighted arithmetic averaging (INULWAA) and the interval neutrosophic uncertain linguistic weighted arithmetic averaging (INULWGA) operator are developed, and a multiple attribute decision method with interval neutrosophic uncertain linguistic information was developed.

To do so, the remainder of this paper is set out as follows. Section 2 briefly recall some basic concepts of neutrosophic sets, single valued neutrosophic sets (SVNSs), interval neutrosophic sets (INSs), interval neutrosophic linguistic variables and interval neutrosophic uncertain linguistic variables. In section 3, we develop an extended TOPSIS method for the interval neutrosophic uncertain linguistic variables, In section 4, we give an application example to show the decision making steps, In section 5, a comparison with existing methods are presented. Finally, section 6 concludes the paper.

## II-Preliminaries

In the following, we shall introduce some basic concepts related to uncertain linguistic variables, single valued neutrosophic set, interval neutrosophic sets, interval neutrosophic uncertain linguistic sets, and interval neutrosophic uncertain linguistic set.

### 2.1 Neutrosophic sets

Definition 2.1 [7]

Let  $U$  be a universe of discourse then the neutrosophic set  $A$  is an object having the form

$$A = \{ \langle x: T_A(x), I_A(x), F_A(x) \rangle, x \in X \},$$

Where the functions  $T_A(x), I_A(x), F_A(x): U \rightarrow ]0,1+[$  define respectively the degree of membership, the degree of indeterminacy, and the degree of non-membership of the element  $x \in X$  to the set  $A$  with the condition.

$$0 \leq \sup T_A(x) + \sup I_A(x) + \sup F_A(x) \leq 3^+. \quad (1)$$

From philosophical point of view, the neutrosophic set takes the value from real standard or non-standard subsets of  $]0,1+[$ . So instead of  $]0,1+[$  we need to take the interval  $[0,1]$  for technical applications, because  $]0,1+[$  will be difficult to apply in the real applications such as in scientific and engineering problems.

### 2.2 Single valued Neutrosophic Sets

Definition 2.2 [8]

Let  $X$  be a universe of discourse, then the neutrosophic set  $A$  is an object having the form

$$A = \{ \langle x: T_A(x), I_A(x), F_A(x) \rangle, x \in X \},$$

where the functions  $T_A(x), I_A(x), F_A(x): U \rightarrow [0,1]$  define respectively the degree of membership, the degree of indeterminacy, and the degree of non-membership of the

element  $x \in X$  to the set  $A$  with the condition.

$$0 \leq T_A(x) + I_A(x) + F_A(x) \leq 3 \quad (2)$$

**Definition 2.3 [8]**

A single valued neutrosophic set  $A$  is contained in another single valued neutrosophic set  $B$  i.e.  $A \subseteq B$  if  $\forall x \in U, T_A(x) \leq T_B(x), I_A(x) \geq I_B(x), F_A(x) \geq F_B(x)$ .

(3)

**2.3 Interval Neutrosophic Sets**

Definition 2.4[9]

Let  $X$  be a space of points (objects) with generic elements in  $X$  denoted by  $x$ . An interval valued neutrosophic set (for short IVNS)  $A$  in  $X$  is characterized by truth-membership function  $T_A(x)$ , indeterminacy-membership function  $I_A(x)$  and falsity-membership function  $F_A(x)$ . For each point  $x$  in  $X$ , we have that  $T_A(x), I_A(x), F_A(x) \subseteq [0, 1]$ .

For two IVNS,  $A_{IVNS} = \{ \langle x, [T_A^L(x), T_A^U(x)], [I_A^L(x), I_A^U(x)], [F_A^L(x), F_A^U(x)] \rangle \mid x \in X \}$  (4)

And  $B_{IVNS} = \{ \langle x, [T_B^L(x), T_B^U(x)], [I_B^L(x), I_B^U(x)], [F_B^L(x), F_B^U(x)] \rangle \mid x \in X \}$  the two relations are defined as follows:

(1)  $A_{IVNS} \subseteq B_{IVNS}$  If and only if  $T_A^L(x) \leq T_B^L(x), T_A^U(x) \leq T_B^U(x), I_A^L(x) \geq I_B^L(x), I_A^U(x) \geq I_B^U(x), F_A^L(x) \geq F_B^L(x), F_A^U(x) \geq F_B^U(x)$

(2)  $A_{IVNS} = B_{IVNS}$  if and only if,  $T_A(x) = T_B(x), I_A(x) = I_B(x), F_A(x) = F_B(x)$  for any  $x \in X$

The complement of  $A_{IVNS}$  is denoted by  $A_{IVNS}^o$  and is defined by

$$A_{IVNS}^o = \{ \langle x, [F_A^L(x), F_A^U(x)], [1 - I_A^U(x), 1 - I_A^L(x)], [T_A^L(x), T_A^U(x)] \rangle \mid x \in X \}$$

$$A \cap B = \{ \langle x, [\min(T_A^L(x), T_B^L(x)), \min(T_A^U(x), T_B^U(x))], [\max(I_A^L(x), I_B^L(x)), \max(I_A^U(x), I_B^U(x))], [\max(F_A^L(x), F_B^L(x)), \max(F_A^U(x), F_B^U(x))] \rangle \mid x \in X \}$$

$$A \cup B = \{ \langle x, [\max(T_A^L(x), T_B^L(x)), \max(T_A^U(x), T_B^U(x))], [\min(I_A^L(x), I_B^L(x)), \min(I_A^U(x), I_B^U(x))], [\min(F_A^L(x), F_B^L(x)), \min(F_A^U(x), F_B^U(x))] \rangle \mid x \in X \}$$

**2.4 Uncertain linguistic variable.**

A linguistic set is defined as a finite and completely ordered discrete term set,

$S = \{s_0, s_1, \dots, s_{l-1}\}$ , where  $l$  is the odd value. For example, when  $l=7$ , the linguistic term set  $S$  can be defined as follows:  $S = \{s_0(\text{extremely low}); s_1(\text{very low}); s_2(\text{low}); s_3(\text{medium}); s_4(\text{high}); s_5(\text{very high}); s_6(\text{extremely high})\}$

**Definition 2.5.** Suppose  $\tilde{s} = [s_a, s_b]$ , where  $s_a, s_b \in \tilde{S}$  with  $a \leq b$  are the lower limit and the upper limit of  $\tilde{S}$ ,

respectively. Then  $\tilde{s}$  is called an uncertain linguistic variable.

**Definition 2.6.** Suppose  $\tilde{s}_1 = [s_{a_1}, s_{b_1}]$  and  $\tilde{s}_2 = [s_{a_2}, s_{b_2}]$  are two uncertain linguistic variable, then the distance between  $\tilde{s}_1$  and  $\tilde{s}_2$  is defined as follows.

$$d(\tilde{s}_1, \tilde{s}_2) = \frac{1}{2(l-1)} (|a_2 - a_1| + |b_2 - b_1|) \quad (5)$$

**2.5 Interval neutrosophic linguistic set**

Based on interval neutrosophic set and linguistic variables, J. Ye [18] presented the extension form of the linguistic set, i.e, interval neutrosophic linguistic set, which is shown as follows:

**Definition 2.7 :[19]** An interval neutrosophic linguistic set  $A$  in  $X$  can be defined as

$$A = \{ \langle x, s_{\theta(x)}, (T_A(x), I_A(x), F_A(x)) \rangle \mid x \in X \} \quad (6)$$

Where  $s_{\theta(x)} \in \hat{S}, T_A(x) = [T_A^L(x), T_A^U(x)] \subseteq [0, 1], I_A(x) = [I_A^L(x), I_A^U(x)] \subseteq [0, 1]$ , and  $F_A(x) = [F_A^L(x), F_A^U(x)] \subseteq [0, 1]$  with the condition  $0 \leq T_A^U(x) + I_A^U(x) + F_A^U(x) \leq 3$  for any  $x \in X$ . The function  $T_A(x), I_A(x)$  and  $F_A(x)$  express, respectively, the truth-membership degree, the indeterminacy –membership degree, and the falsity-membership degree with interval values of the element  $x$  in  $X$  to the linguistic variable  $s_{\theta(x)}$ .

**2.6 Interval neutrosophic uncertain linguistic set.**

Based on interval neutrosophic set and uncertain linguistic variables, J.Ye [20] presented the extension form of the uncertain linguistic set, i.e, interval neutrosophic uncertain linguistic set, which is shown as follows:

**Definition 2.8 :[20]** An interval neutrosophic uncertain linguistic set  $A$  in  $X$  can be defined as

$$A = \{ \langle x, [s_{\theta(x)}, s_{\rho(x)}], (T_A(x), I_A(x), F_A(x)) \rangle \mid x \in X \} \quad (7)$$

Where  $s_{\theta(x)} \in \hat{S}, T_A(x) = [T_A^L(x), T_A^U(x)] \subseteq [0, 1], I_A(x) = [I_A^L(x), I_A^U(x)] \subseteq [0, 1]$ , and  $F_A(x) = [F_A^L(x), F_A^U(x)] \subseteq [0, 1]$  with the condition  $0 \leq T_A^U(x) + I_A^U(x) + F_A^U(x) \leq 3$  for any  $x \in X$ . The function  $T_A(x), I_A(x)$  and  $F_A(x)$  express, respectively, the truth-membership degree, the indeterminacy–membership degree, and the falsity-membership degree with interval values of the element  $x$  in  $X$  to the uncertain linguistic variable  $[s_{\theta(x)}, s_{\rho(x)}]$ .

**Definition 2.9** Let  $\tilde{a}_1 = \langle [s_{\theta(\tilde{a}_1)}, s_{\rho(\tilde{a}_1)}], ([T^L(\tilde{a}_1), T^U(\tilde{a}_1)], [I^L(\tilde{a}_1), I^U(\tilde{a}_1)], [F^L(\tilde{a}_1), F^U(\tilde{a}_1)]) \rangle$  and  $\tilde{a}_2 = \langle x, [s_{\theta(\tilde{a}_2)}, s_{\rho(\tilde{a}_2)}], ([T^L(\tilde{a}_2), T^U(\tilde{a}_2)], [I^L(\tilde{a}_2), I^U(\tilde{a}_2)], [F^L(\tilde{a}_2), F^U(\tilde{a}_2)]) \rangle$

be two INULVs and  $\lambda \geq 0$ , then the operational laws of INULVs are defined as follows:

$$\tilde{a}_1 \oplus \tilde{a}_2 = \langle [s_{\theta(\tilde{a}_1)+\theta(\tilde{a}_2)}, s_{\rho(\tilde{a}_1)+\rho(\tilde{a}_2)}], ([T^L(\tilde{a}_1)+T^L(\tilde{a}_2)-T^L(\tilde{a}_1)T^L(\tilde{a}_2), T^U(\tilde{a}_1)+T^U(\tilde{a}_2)-T^U(\tilde{a}_1)T^U(\tilde{a}_2)], [I^L(\tilde{a}_1)I^L(\tilde{a}_2), I^U(\tilde{a}_1)I^U(\tilde{a}_2)], [F^L(\tilde{a}_1)F^L(\tilde{a}_2), F^U(\tilde{a}_1)F^U(\tilde{a}_2)]) \rangle \tag{8}$$

$$\tilde{a}_1 \otimes \tilde{a}_2 = \langle [s_{\theta(\tilde{a}_1) \times \theta(\tilde{a}_2)}], ([T^L(\tilde{a}_1)T^L(\tilde{a}_2), T^U(\tilde{a}_1)T^U(\tilde{a}_2)], [I^L(\tilde{a}_1)+I^L(\tilde{a}_2)-I^L(\tilde{a}_1)I^L(\tilde{a}_2), I^U(\tilde{a}_1)+I^U(\tilde{a}_2)-I^U(\tilde{a}_1)I^U(\tilde{a}_2)], [F^L(\tilde{a}_1)+F^L(\tilde{a}_2)-F^L(\tilde{a}_1)F^L(\tilde{a}_2), F^U(\tilde{a}_1)+F^U(\tilde{a}_2)-F^U(\tilde{a}_1)F^U(\tilde{a}_2)]) \rangle \tag{9}$$

$$\lambda \tilde{a}_1 = \langle [s_{\lambda \theta(\tilde{a}_1)}, s_{\lambda \rho(\tilde{a}_1)}], ([1-(1-T^L(\tilde{a}_1))^\lambda, 1-(1-T^U(\tilde{a}_1))^\lambda], [(I^L(\tilde{a}_1))^\lambda, (I^U(\tilde{a}_1))^\lambda], [(F^L(\tilde{a}_1))^\lambda, (F^U(\tilde{a}_1))^\lambda]) \rangle$$

$$\tilde{a}_1^\lambda = \langle [s_{\theta^\lambda(\tilde{a}_1)}, s_{\rho^\lambda(\tilde{a}_1)}], ([ (T^L(\tilde{a}_1))^\lambda, (T^U(\tilde{a}_1))^\lambda ], [1-(1-I^L(\tilde{a}_1))^\lambda, 1-(1-I^U(\tilde{a}_1))^\lambda], [1-(1-F^L(\tilde{a}_1))^\lambda, 1-(1-F^U(\tilde{a}_1))^\lambda]) \rangle \tag{11}$$

Obviously, the above operational results are still INULVs.

### III. The Extended TOPSIS for the Interval Neutrosophic Uncertain Linguistic Variables

A. The description of decision making problems with interval neutrosophic uncertain linguistic information.

For the MADM problems with interval neutrosophic uncertain variables, there are m alternatives  $A = (A_1, A_2, \dots, A_m)$  which can be evaluated by n attributes  $C = (C_1, C_2, \dots, C_n)$  and the weight of attributes  $A_i$  is  $w_i$ , and meets the conditions  $0 \leq w_i \leq 1, \sum_{j=1}^n w_j = 1$ . Suppose  $z_{ij}$  ( $i=1, 2, \dots, n; j=1, 2, \dots, m$ ) is the evaluation values of alternative  $A_i$  with respect to attribute  $C_j$

And it can be represented by interval neutrosophic uncertain linguistic variable  $z_{ij} = \langle [x_{ij}^L, x_{ij}^U], ([T_{ij}^L, T_{ij}^U], [I_{ij}^L, I_{ij}^U], [F_{ij}^L, F_{ij}^U]) \rangle$ , where  $[x_{ij}^L, x_{ij}^U]$  is the uncertain linguistic variable, and  $x_{ij}^L, x_{ij}^U \in S, S = (s_0, s_1, \dots, s_{l-1}), T_{ij}^L, T_{ij}^U, I_{ij}^L, I_{ij}^U$  and  $F_{ij}^L, F_{ij}^U \in [0, 1]$  and  $0 \leq T_{ij}^U + I_{ij}^U + F_{ij}^U \leq 3$ . Suppose attribute weight vector  $W = (w_1, w_2, \dots, w_n)$  is completely unknown, according to these condition, we can rank the alternatives  $(A_1, A_2, \dots, A_m)$

#### B. Obtain the attribute weight vector by the maximizing deviation.

$$d_{IVNS}(\tilde{s}_1, \tilde{s}_3) = \frac{1}{12(l-1)} (|a_1 \times T_A^L - a_3 \times T_C^L| + |a_1 \times T_A^U - a_3 \times T_C^U| + |a_1 \times I_A^L - a_3 \times I_C^L| + |a_1 \times I_A^U - a_3 \times I_C^U| + |a_1 \times F_A^L - a_3 \times F_C^L| + |a_1 \times F_A^U - a_3 \times F_C^U| + |b_1 \times T_A^L - b_3 \times T_C^L| + |b_1 \times T_A^U - b_3 \times T_C^U| + |b_1 \times I_A^L - b_3 \times I_C^L| + |b_1 \times I_A^U - b_3 \times I_C^U| + |b_1 \times F_A^L - b_3 \times F_C^L| + |b_1 \times F_A^U - b_3 \times F_C^U|)$$

In order to obtain the attribute weight vector, we firstly define the distance between two interval neutrosophic uncertain variables.

#### Definition 3.1

Let  $\tilde{s}_1 = \langle [s_{a_1}, s_{b_1}], ([T_A^L, T_A^U], [I_A^L, I_A^U], [F_A^L, F_A^U]) \rangle$ ,  $\tilde{s}_2 = \langle [s_{a_2}, s_{b_2}], ([T_B^L, T_B^U], [I_B^L, I_B^U], [F_B^L, F_B^U]) \rangle$  and  $\tilde{s}_3 = \langle [s_{a_3}, s_{b_3}], ([T_C^L, T_C^U], [I_C^L, I_C^U], [F_C^L, F_C^U]) \rangle$ , be any three interval neutrosophic uncertain linguistic variables, and  $\tilde{S}$  be the set of linguistic variables,  $f$  is a map, and  $f: \tilde{S} \times \tilde{S} \rightarrow \mathbb{R}$ . If  $d(\tilde{s}_1, \tilde{s}_2)$  meets the following conditions

- (1)  $0 \leq d_{INULV}(\tilde{s}_1, \tilde{s}_2) \leq 1, d_{INULV}(\tilde{s}_1, \tilde{s}_1) = 0$
- (2)  $d_{INULV}(\tilde{s}_1, \tilde{s}_2) = d_{INULV}(\tilde{s}_2, \tilde{s}_1)$
- (3)  $d_{IVNS}(\tilde{s}_1, \tilde{s}_2) + d_{INULV}(\tilde{s}_2, \tilde{s}_3) \geq d_{INULV}(\tilde{s}_1, \tilde{s}_3)$

then  $d_{INULV}(\tilde{s}_1, \tilde{s}_2)$  is called the distance between two interval neutrosophic uncertain linguistic variables  $\tilde{s}_1$

#### Definition 3.2:

Let  $\tilde{s}_1 = \langle [s_{a_1}, s_{b_1}], ([T_A^L, T_A^U], [I_A^L, I_A^U], [F_A^L, F_A^U]) \rangle$ , and  $\tilde{s}_2 = \langle [s_{a_2}, s_{b_2}], ([T_B^L, T_B^U], [I_B^L, I_B^U], [F_B^L, F_B^U]) \rangle$ , be any two interval neutrosophic uncertain linguistic variables, then the Hamming distance between  $\tilde{s}_1$  and  $\tilde{s}_2$  can be defined as follows.

$$d_{INULV}(\tilde{s}_1, \tilde{s}_2) = \frac{1}{12(l-1)} (|a_1 \times T_A^L - a_2 \times T_B^L| + |a_1 \times T_A^U - a_2 \times T_B^U| + |a_1 \times I_A^L - a_2 \times I_B^L| + |a_1 \times I_A^U - a_2 \times I_B^U| + |a_1 \times F_A^L - a_2 \times F_B^L| + |a_1 \times F_A^U - a_2 \times F_B^U| + |b_1 \times T_A^L - b_2 \times T_B^L| + |b_1 \times T_A^U - b_2 \times T_B^U| + |b_1 \times I_A^L - b_2 \times I_B^L| + |b_1 \times I_A^U - b_2 \times I_B^U| + |b_1 \times F_A^L - b_2 \times F_B^L| + |b_1 \times F_A^U - b_2 \times F_B^U|) \tag{12}$$

In order to illustrate the effectiveness of definition 3.2, the distance defined above must meet the three conditions in definition 3.1

#### Proof

Obviously, the distance defined in (12) can meets the conditions (1) and (2) in definition 3.1

In the following, we will prove that the distance defined in (12) can also meet the condition (3) in definition 3.1

For any one interval neutrosophic uncertain linguistic variable  $\tilde{s}_3 = \langle [s_{a_3}, s_{b_3}], ([T_C^L, T_C^U], [I_C^L, I_C^U], [F_C^L, F_C^U]) \rangle$ ,

$$\begin{aligned}
 &= \frac{1}{12(l-1)} (|a_1 \times T_A^L - a_2 \times T_B^L + a_2 \times T_B^L - a_3 \times T_C^L| + |a_1 \times T_A^U - a_2 \times T_B^U + a_2 \times T_B^U - a_3 \times T_C^U| + |a_1 \times I_A^L - a_2 \times I_B^L + a_2 \times I_B^L - a_3 \times I_C^L| + |a_1 \times I_A^U - a_2 \times I_B^U + a_2 \times I_B^U - a_3 \times I_C^U| \\
 &+ |a_1 \times F_A^L - a_2 \times F_B^L + a_2 \times F_B^L - a_3 \times F_C^L| + |a_1 \times F_A^U - a_2 \times F_B^U + a_2 \times F_B^U - a_3 \times F_C^U| \\
 &+ |b_1 \times T_A^L - b_2 \times T_B^L + b_2 \times T_B^L - b_3 \times T_C^L| + |b_1 \times T_A^U - b_2 \times T_B^U + b_2 \times T_B^U - b_3 \times T_C^U| + |b_1 \times I_A^L - b_2 \times I_B^L + b_2 \times I_B^L - b_3 \times I_C^L| + |b_1 \times I_A^U - b_2 \times I_B^U + b_2 \times I_B^U - b_3 \times I_C^U| \\
 &+ |b_1 \times F_A^L - b_2 \times F_B^L + b_2 \times F_B^L - a_3 \times F_C^L| + |b_1 \times F_A^U - b_2 \times F_B^U + b_2 \times F_B^U - b_3 \times F_C^U|
 \end{aligned}$$

And

$$\frac{1}{12(l-1)} (|a_1 \times T_A^L - a_2 \times T_B^L| + |a_2 \times T_B^L - a_3 \times T_C^L| + |a_1 \times T_A^U - a_2 \times T_B^U| + |a_2 \times T_B^U - a_3 \times T_C^U| + |a_1 \times I_A^L - a_2 \times I_B^L| + |a_2 \times I_B^L - a_3 \times I_C^L| + |a_1 \times I_A^U - a_2 \times I_B^U| + |a_2 \times I_B^U - a_3 \times I_C^U| +$$

$$|a_1 \times F_A^L - a_2 \times F_B^L| + |a_2 \times F_B^L - a_3 \times F_C^L| + |a_1 \times F_A^U - a_2 \times F_B^U| + |a_2 \times F_B^U - a_3 \times F_C^U| +$$

$$+ |b_2 \times T_B^L - b_3 \times T_C^L| + |b_1 \times T_A^U - b_2 \times T_B^U| + |b_2 \times T_B^U - b_3 \times T_C^U| + |b_1 \times I_A^L - b_2 \times I_B^L| + |b_2 \times I_B^L - b_3 \times I_C^L| + |b_1 \times I_A^U - b_2 \times I_B^U| + |b_2 \times I_B^U - b_3 \times I_C^U| + |b_1 \times F_A^L - b_2 \times F_B^L| + |b_2 \times F_B^L - b_3 \times F_C^L| + |b_1 \times F_A^U - b_2 \times F_B^U| + |b_2 \times F_B^U - b_3 \times F_C^U|)$$

$$\begin{aligned}
 &= \frac{1}{12(l-1)} (|a_1 \times T_A^L - a_2 \times T_B^L| + |a_1 \times T_A^U - a_2 \times T_B^U| + |a_1 \times I_A^L - a_2 \times I_B^L| + |a_1 \times I_A^U - a_2 \times I_B^U| + |a_1 \times F_A^L - a_2 \times F_B^L| + |a_1 \times F_A^U - a_2 \times F_B^U| + |b_1 \times T_A^L - b_2 \times T_B^L| + |b_1 \times T_A^U - b_2 \times T_B^U| + |b_1 \times I_A^L - b_2 \times I_B^L| + |b_1 \times I_A^U - b_2 \times I_B^U| + |b_1 \times F_A^L - b_2 \times F_B^L| + |b_1 \times F_A^U - b_2 \times F_B^U| + \\
 &|a_2 \times T_B^L - a_3 \times T_C^L| + |a_2 \times T_B^U - a_3 \times T_C^U| + |a_2 \times I_B^L - a_3 \times I_C^L| + |a_2 \times I_B^U - a_3 \times I_C^U| + |a_2 \times F_B^L - a_3 \times F_C^L| + |a_2 \times F_B^U - a_3 \times F_C^U| + |b_2 \times T_B^L - b_3 \times T_C^L| + |b_2 \times T_B^U - b_3 \times T_C^U| + |b_2 \times I_B^L - b_3 \times I_C^L| + |b_2 \times I_B^U - b_3 \times I_C^U| + |b_2 \times F_B^L - b_3 \times F_C^L| + |b_2 \times F_B^U - b_3 \times F_C^U|)
 \end{aligned}$$

$$\begin{aligned}
 &= \frac{1}{12(l-1)} (|a_1 \times T_A^L - a_2 \times T_B^L| + |a_1 \times T_A^U - a_2 \times T_B^U| + |a_1 \times I_A^L - a_2 \times I_B^L| + |a_1 \times I_A^U - a_2 \times I_B^U| + |a_1 \times F_A^L - a_2 \times F_B^L| + |a_1 \times F_A^U - a_2 \times F_B^U| + |b_1 \times T_A^L - b_2 \times T_B^L| + |b_1 \times T_A^U - b_2 \times T_B^U| + |b_1 \times I_A^L - b_2 \times I_B^L| + |b_1 \times I_A^U - b_2 \times I_B^U| + |b_1 \times F_A^L - b_2 \times F_B^L| + |b_1 \times F_A^U - b_2 \times F_B^U| + \\
 &\frac{1}{12(l-1)} (|a_2 \times T_B^L - a_3 \times T_C^L| + |a_2 \times T_B^U - a_3 \times T_C^U| + |a_2 \times I_B^L - a_3 \times I_C^L| + |a_2 \times I_B^U - a_3 \times I_C^U| + |a_2 \times F_B^L - a_3 \times F_C^L| + |a_2 \times F_B^U - a_3 \times F_C^U| + |b_2 \times T_B^L - b_3 \times T_C^L| + |b_2 \times T_B^U - b_3 \times T_C^U| + |b_2 \times I_B^L - b_3 \times I_C^L| + |b_2 \times I_B^U - b_3 \times I_C^U| + |b_2 \times F_B^L - b_3 \times F_C^L| + |b_2 \times F_B^U - b_3 \times F_C^U|)
 \end{aligned}$$

$$= d_{INULV}(\tilde{s}_1, \tilde{s}_2) + d_{INULV}(\tilde{s}_2, \tilde{s}_3)$$

$$\text{So, } d_{INULV}(\tilde{s}_1, \tilde{s}_2) + d_{INULV}(\tilde{s}_2, \tilde{s}_3) \geq d_{INULV}(\tilde{s}_1, \tilde{s}_3)$$

Especially, when  $T_A^L=T_A^U$ ,  $I_A^L=I_A^U$ ,  $F_A^L=F_A^U$ , and  $T_B^L=T_B^U$ ,  $I_B^L=I_B^U$ , and  $F_B^L=F_B^U$  the interval neutrosophic uncertain linguistic variables  $\tilde{s}_1, \tilde{s}_2$  can be reduced to single valued uncertain linguistic variables. So the single valued neutrosophic uncertain linguistic variables are the special case of the interval neutrosophic uncertain linguistic variables.

Because the attribute weight is fully unknown, we can obtain the attribute weight vector by the maximizing deviation method. Its main idea can be described as follows. If all attribute values  $z_{ij}$  ( $j=1, 2, \dots, n$ ) in the attribute  $C_j$  have a small difference for all alternatives, it shows that the attribute  $C_j$  has a small importance in ranking all alternatives, and it can be assigned a small attribute weight, especially, if all attribute values  $z_{ij}$  ( $j=1,$

$2, \dots, n$ ) in the attribute  $C_j$  are equal, then the attribute  $C_j$  has no effect on sorting, and we can set zero to the weight of attribute  $C_j$ . On the contrary, if all attribute values  $z_{ij}$  ( $j=1, 2, \dots, n$ ) in the attribute  $C_j$  have a big difference, the attribute  $C_j$  will have a big importance in ranking all alternatives, and its weight can be assigned a big value.

Here, based on the maximizing deviation method, we construct an optimization model to determine the optimal relative weights of criteria under interval neutrosophic uncertain linguistic environment. For the criterion  $C_i \in C$ , we can use the distance  $d(z_{ij}, z_{kj})$  to represent the deviation between attribute values  $z_{ij}$  and  $z_{kj}$ , and  $D_{ij} = \sum_{k=1}^m d(z_{ij}, z_{kj}) w_j$  can present the weighted deviation sum for the alternative  $A_i$  to all alternatives, then

$D_j(w_j) = \sum_{i=1}^m D_{ij}(w_j) = \sum_{i=1}^m \sum_{k=1}^m d(z_{ij}, z_{kj}) w_j$  presents the weighted deviation sum for all alternatives,  $D(w_j) = \sum_{j=1}^n D_j(w_j) = \sum_{j=1}^n \sum_{i=1}^m \sum_{k=1}^m d(z_{ij}, z_{kj}) w_j$ , presents total weighted deviations for all alternatives with respect to all attributes.

Based on the above analysis, we can construct a non linear programming model to select the weight vector  $w$  by maximizing  $D(w)$ , as follow:

$$\begin{cases} \text{Max } D(w_j) = \sum_{j=1}^n \sum_{i=1}^m \sum_{k=1}^m d(z_{ij}, z_{kj}) w_j \\ \text{s. t } \sum_{j=1}^n w_j^2, w_j \in [0, 1], j = 1, 2, \dots, n \end{cases} \quad (13)$$

Then we can build Lagrange multiplier function, and get

$$L(w_j, \lambda) = \sum_{j=1}^n \sum_{i=1}^m \sum_{k=1}^m d(z_{ij}, z_{kj}) w_j + \lambda (\sum_{j=1}^n w_j^2 - 1)$$

$$\text{Let } \begin{cases} \frac{\partial L(w_j, \lambda)}{\partial w_j} = \sum_{i=1}^m \sum_{k=1}^m d(z_{ij}, z_{kj}) w_j + 2\lambda w_j = 0 \\ \frac{\partial L(w_j, \lambda)}{\partial \lambda} = \sum_{j=1}^n w_j^2 - 1 = 0 \end{cases}$$

We can get

$$\begin{cases} \text{(i) For benefit type,} \\ r_{ij}^L = x_{ij}^L, r_{ij}^U = x_{ij}^U \text{ for } (1 \leq i \leq m, 1 \leq j \leq n) \\ \hat{T}_{ij}^L = T_{ij}^L, \hat{T}_{ij}^U = T_{ij}^U, \hat{I}_{ij}^L = I_{ij}^L, \hat{I}_{ij}^U = I_{ij}^U, \hat{F}_{ij}^L = F_{ij}^L, \hat{F}_{ij}^U = F_{ij}^U \\ \text{(ii) For cost type,} \end{cases} \quad (16)$$

$$\begin{cases} r_{ij}^L = \text{neg}(x_{ij}^U), r_{ij}^U = \text{neg}(x_{ij}^L) \text{ for } (1 \leq i \leq m, 1 \leq j \leq n) \\ \hat{T}_{ij}^L = T_{ij}^L, \hat{T}_{ij}^U = T_{ij}^U, \hat{I}_{ij}^L = I_{ij}^L, \hat{I}_{ij}^U = I_{ij}^U, \hat{F}_{ij}^L = F_{ij}^L, \hat{F}_{ij}^U = F_{ij}^U \end{cases} \quad (17)$$

(2) Construct the weighted normalize matrix

$$Y = [y_{ij}]_{m \times n}$$

$$\begin{bmatrix} < [y_{11}^L, y_{11}^U], ([\hat{T}_{11}^L, \hat{T}_{11}^U], [\hat{I}_{11}^L, \hat{I}_{11}^U], [\hat{F}_{11}^L, \hat{F}_{11}^U]) > & \dots & < [y_{1n}^L, y_{1n}^U], ([\hat{T}_{1n}^L, \hat{T}_{1n}^U], [\hat{I}_{1n}^L, \hat{I}_{1n}^U], [\hat{F}_{1n}^L, \hat{F}_{1n}^U]) > \\ < [y_{21}^L, y_{21}^U], ([\hat{T}_{21}^L, \hat{T}_{21}^U], [\hat{I}_{21}^L, \hat{I}_{21}^U], [\hat{F}_{21}^L, \hat{F}_{21}^U]) > & \dots & < [y_{2n}^L, y_{2n}^U], ([\hat{T}_{2n}^L, \hat{T}_{2n}^U], [\hat{I}_{2n}^L, \hat{I}_{2n}^U], [\hat{F}_{2n}^L, \hat{F}_{2n}^U]) > \\ \dots & \dots & \dots & \dots \\ < [y_{mn}^L, y_{mn}^U], ([\hat{T}_{mn}^L, \hat{T}_{mn}^U], [\hat{I}_{mn}^L, \hat{I}_{mn}^U], [\hat{F}_{mn}^L, \hat{F}_{mn}^U]) > & \dots & < [y_{mn}^L, y_{mn}^U], ([\hat{T}_{mn}^L, \hat{T}_{mn}^U], [\hat{I}_{mn}^L, \hat{I}_{mn}^U], [\hat{F}_{mn}^L, \hat{F}_{mn}^U]) > \end{bmatrix}$$

Where

$$\begin{cases} y_{ij}^L = w_j r_{ij}^L, y_{ij}^U = w_j r_{ij}^U \\ \hat{T}_{ij}^L = 1 - (1 - \hat{T}_{ij}^L)^{w_j}, \hat{T}_{ij}^U = 1 - (1 - \hat{T}_{ij}^U)^{w_j}, \hat{I}_{ij}^L = (\hat{I}_{ij}^L)^{w_j}, \hat{I}_{ij}^U = (\hat{I}_{ij}^U)^{w_j}, \hat{F}_{ij}^L = (\hat{F}_{ij}^L)^{w_j}, \hat{F}_{ij}^U = (\hat{F}_{ij}^U)^{w_j} \end{cases} \quad (18)$$

(3) Identify, the sets of the positive ideal solution  $Y^+ = (y_1^+, y_2^+, \dots, y_m^+)$  and the negative ideal solution  $Y^- = (y_1^-, y_2^-, \dots, y_m^-)$ , then we can get

$$Y^+ = (y_1^+, y_2^+, \dots, y_m^+) = (< [y_1^{L+}, y_1^{U+}], ([\hat{T}_1^{L+}, \hat{T}_1^{U+}], [\hat{I}_1^{L+}, \hat{I}_1^{U+}], [\hat{F}_1^{L+}, \hat{F}_1^{U+}]) >, < [y_2^{L+}, y_2^{U+}], ([\hat{T}_2^{L+}, \hat{T}_2^{U+}], [\hat{I}_2^{L+}, \hat{I}_2^{U+}], [\hat{F}_2^{L+}, \hat{F}_2^{U+}]) >, \dots, < [y_n^{L+}, y_n^{U+}], ([\hat{T}_n^{L+}, \hat{T}_n^{U+}], [\hat{I}_n^{L+}, \hat{I}_n^{U+}], [\hat{F}_n^{L+}, \hat{F}_n^{U+}]) >) \quad (19)$$

$$\begin{cases} 2\lambda = \sqrt{\sum_{j=1}^n (\sum_{i=1}^m \sum_{k=1}^m d(z_{ij}, z_{kj}))^2} \\ w_j = \frac{\sum_{i=1}^m \sum_{k=1}^m d(z_{ij}, z_{kj})}{\sqrt{\sum_{j=1}^n (\sum_{i=1}^m \sum_{k=1}^m d(z_{ij}, z_{kj}))^2}} \end{cases} \quad (14)$$

Then we can get the normalized attribute weight, and have

$$w_j = \frac{\sum_{i=1}^m \sum_{k=1}^m d(z_{ij}, z_{kj})}{\sum_{j=1}^n \sum_{i=1}^m \sum_{k=1}^m d(z_{ij}, z_{kj})} \quad (15)$$

### C. The Extended TOPSIS Method for the Interval Neutrosophic Uncertain linguistic Information.

The standard TOPSIS method can only process the real numbers, and cannot deal with the interval neutrosophic uncertain linguistic information. In the following, we will extend TOPSIS to process the interval neutrosophic uncertain linguistic variables. The steps are shown as follows

(1) Normalize the decision matrix

Considering the benefit or cost type of the attribute values, we can give the normalized matrix  $R = (r_{ij})$ , where  $r_{ij} = \langle [r_{ij}^L, r_{ij}^U], 1, ([\hat{T}_{ij}^L, \hat{T}_{ij}^U], [\hat{I}_{ij}^L, \hat{I}_{ij}^U], [\hat{F}_{ij}^L, \hat{F}_{ij}^U]) \rangle$ . The normalization can be made shown as follows.

$$Y^- = (y_1^-, y_2^-, \dots, y_m^-) = \langle [y_1^{L-}, y_1^{U-}], ([\tilde{T}_1^{L-}, \tilde{T}_1^{U-}], [\tilde{I}_1^{L-}, \tilde{I}_1^{U-}], [\tilde{F}_1^{L-}, \tilde{F}_1^{U-}]) \rangle, \dots, \langle [y_n^{L-}, y_n^{U-}], ([\tilde{T}_n^{L-}, \tilde{T}_n^{U-}], [\tilde{I}_n^{L-}, \tilde{I}_n^{U-}], [\tilde{F}_n^{L-}, \tilde{F}_n^{U-}]) \rangle \tag{20}$$

Where

$$\left\{ \begin{aligned} y_j^{L+} &= \max_i(y_{ij}^L), y_j^{U+} = \max_i(y_{ij}^U), \\ \tilde{T}_j^{L+} &= \max_i(\tilde{T}_{ij}^L), \tilde{T}_j^{U+} = \max_i(\tilde{T}_{ij}^U), \tilde{I}_j^{L+} = \min_i(\tilde{I}_{ij}^L), \tilde{I}_j^{U+} = \min_i(\tilde{I}_{ij}^U), \tilde{F}_j^{L+} = \min_i(\tilde{F}_{ij}^L), \tilde{F}_j^{U+} = \min_i(\tilde{F}_{ij}^U), \\ y_j^{L-} &= \min_i(y_{ij}^L), y_j^{U-} = \min_i(y_{ij}^U), \\ \tilde{T}_j^{L-} &= \min_i(\tilde{T}_{ij}^L), \tilde{T}_j^{U-} = \min_i(\tilde{T}_{ij}^U), \tilde{I}_j^{L-} = \max_i(\tilde{I}_{ij}^L), \tilde{I}_j^{U-} = \max_i(\tilde{I}_{ij}^U), \tilde{F}_j^{L-} = \max_i(\tilde{F}_{ij}^L), \tilde{F}_j^{U-} = \max_i(\tilde{F}_{ij}^U), \end{aligned} \right. \tag{21}$$

- (4) Obtain the distance between each alternative and the positive ideal solution, and between each alternative and the negative ideal solution, then we can get

$$\begin{aligned} D^+ &= (d_1^+, d_2^+, \dots, d_m^+) \\ D^- &= (d_1^-, d_2^-, \dots, d_m^-) \end{aligned} \tag{22}$$

Where,

$$\left\{ \begin{aligned} d_i^+ &= \left[ \sum_{j=1}^n (d(y_{ij}, y_j^+))^2 \right]^{\frac{1}{2}} \\ d_i^- &= \left[ \sum_{j=1}^n (d(y_{ij}, y_j^-))^2 \right]^{\frac{1}{2}} \end{aligned} \right. \tag{23}$$

Where,  $d(y_{ij}, y_j^+)$  is the distance between the interval valued neutrosophic uncertain linguistic variables  $y_{ij}$  and  $y_j^+$  and  $d(y_{ij}, y_j^-)$  is the distance between the interval valued neutrosophic uncertain linguistic variables  $y_{ij}$  and  $y_j^-$  which can be calculated by (12)

- (5) Obtain the closeness coefficients of each alternative to the ideal solution, and then we can get

$$cc_i = \frac{d_i^+}{d_i^+ + d_i^-} \quad (i=1, 2, \dots, m) \tag{24}$$

- (6) Rank the alternatives

According to the closeness coefficient above, we can choose an alternative with minimum  $cc_i$  or rank alternatives according to  $cc_i$  in ascending order

**IV. An illustrative example**

In this part, we give an illustrative example adapted from J. Ye [20] for the extended TOPSIS method to multiple

$$(R)_{m \times n} =$$

$$\left[ \begin{aligned} &\langle ([s_4, s_5], [0.4, 0.5], [0.2, 0.3], [0.3, 0.4]) \rangle && \langle ([s_5, s_6], [0.4, 0.6], [0.1, 0.2], [0.2, 0.4]) \rangle && \langle ([s_4, s_5], [0.2, 0.3], [0.1, 0.2], [0.5, 0.6]) \rangle \\ &\langle ([s_5, s_6], [0.5, 0.7], [0.1, 0.2], [0.2, 0.3]) \rangle && \langle ([s_4, s_5], [0.6, 0.7], [0.1, 0.2], [0.2, 0.3]) \rangle && \langle ([s_4, s_5], [0.5, 0.7], [0.2, 0.2], [0.1, 0.2]) \rangle \\ &\langle ([s_5, s_6], [0.3, 0.5], [0.1, 0.2], [0.3, 0.4]) \rangle && \langle ([s_5, s_6], [0.5, 0.6], [0.1, 0.3], [0.3, 0.4]) \rangle && \langle ([s_4, s_4], [0.5, 0.6], [0.1, 0.3], [0.1, 0.3]) \rangle \\ &\langle ([s_3, s_4], [0.7, 0.8], [0.0, 0.1], [0.1, 0.2]) \rangle && \langle ([s_3, s_4], [0.5, 0.7], [0.1, 0.2], [0.2, 0.3]) \rangle && \langle ([s_5, s_6], [0.3, 0.4], [0.1, 0.2], [0.1, 0.2]) \rangle \end{aligned} \right]$$

**A. Decision steps**

attribute decision making problems in which the attribute values are the interval neutrosophic uncertain linguistic variables.

Suppose that an investment company, wants to invest a sum of money in the best option. To invest the money, there is a panel with four possible alternatives: (1)  $A_1$  is car company; (2)  $A_2$  is food company; (3)  $A_3$  is a computer company; (4)  $A_4$  is an arms company. The investment company must take a decision according to the three attributes: (1)  $C_1$  is the risk; (2)  $C_2$  is the growth; (3)  $C_3$  is the environmental impact. The weight vector of the attributes is  $\omega = (0.35, 0.25, 0.4)^T$ . The expert evaluates the four possible alternatives of  $A_i$  ( $i=1,2,3,4$ ) with respect to the three attributes of  $C_j$  ( $j=1,2,3$ ), where the evaluation information is expressed by the form of INULV values under the linguistic term set  $S = \{s_0 = \text{extremely poor}, s_1 = \text{very poor}, s_2 = \text{poor}, s_3 = \text{medium}, s_4 = \text{good}, s_5 = \text{very good}, s_6 = \text{extremely good}\}$ .

The evaluation information of an alternative  $A_i$  ( $i=1, 2, 3$ ) with respect to an attribute  $C_j$  ( $j=1, 2, 3$ ) can be given by the expert. For example, the INUL value of an alternative  $A_1$  with respect to an attribute  $C_1$  is given as  $\langle [s_4, s_5], [0.4, 0.5], [0.2, 0.3], [0.3, 0.4] \rangle$  by the expert, which indicates that the mark of the alternative  $A_1$  with respect to the attribute  $C_1$  is about the uncertain linguistic value  $[s_4, s_5]$  with the satisfaction degree interval  $[0.4, 0.5]$ , indeterminacy degree interval  $[0.2, 0.3]$ , and dissatisfaction degree interval  $[0.3, 0.4]$ . similarly, the four possible alternatives with respect to the three attributes can be evaluated by the expert, thus we can obtain the following interval neutrosophic uncertain linguistic decision matrix:

To get the best alternatives, the following steps are involved:



**Step 1: Normalization**

Because the attributes are all the benefit types, we don't need the normalization of the decision matrix X

**Step 2: Determine the attribute weight vector W, by formula (24), we can get**

$$Y = \begin{bmatrix} \langle ([s_{1.508}, s_{1.885}], ([0.175, 0.229], [0.545, 0.635], [0.635, 0.708])) \rangle & \langle ([s_{1.225}, s_{1.467}], ([0.117, 0.201], [0.570, 0.675], [0.675, 0.800])) \rangle \\ \langle ([s_{1.885}, s_{2.262}], ([0.229, 0.365], [0.42, 0.545], [0.545, 0.635])) \rangle & \langle ([s_{0.98}, s_{1.225}], ([0.201, 0.255], [0.570, 0.675], [0.675, 0.745])) \rangle \\ \langle ([s_{1.885}, s_{2.262}], ([0.125, 0.23], [0.42, 0.545], [0.635, 0.708])) \rangle & \langle ([s_{0.98}, s_{1.225}], ([0.156, 0.201], [0.570, 0.745], [0.745, 0.800])) \rangle \\ \langle ([s_{1.131}, s_{1.508}], ([0.364, 0.455], [0.0, 0.42], [0.42, 0.545])) \rangle & \langle ([s_{0.735}, s_{0.98}], ([0.156, 0.255], [0.570, 0.674], [0.675, 0.745])) \rangle \\ \\ \langle ([s_{1.508}, s_{1.885}], ([0.081, 0.126], [0.420, 0.545], [0.77, 0.825])) \rangle & \\ \langle ([s_{1.508}, s_{1.885}], ([0.231, 0.365], [0.545, 0.545], [0.420, 0.545])) \rangle & \\ \langle ([s_{1.508}, s_{1.508}], ([0.231, 0.292], [0.420, 0.635], [0.420, 0.635])) \rangle & \\ \langle ([s_{1.885}, s_{2.262}], ([0.126, 0.175], [0.420, 0.545], [0.420, 0.545])) \rangle & \end{bmatrix}$$

$$w_1 = 0.337, w_2 = 0.244, w_3 = 0.379$$

**Step 3: Construct the weighted normalized matrix, by formula (18), we can get**

**Step 4: Identify the sets of the positive ideal solution**

$Y^+ = (y_1^+, y_2^+, y_3^+)$  and the negative ideal solution

$Y^- = (y_1^-, y_2^-, y_3^-)$ , by formulas (19)- (21), we can get then we can get

$$Y^+ = (\langle ([s_{1.885}, s_{2.262}], ([0.365, 0.455], [0, 0.42], [0.42, 0.545])) \rangle, \langle ([s_{1.225}, s_{1.47}], ([0.201, 0.255], [0.569, 0.674], [0.674, 0.745])) \rangle, \langle ([s_{1.885}, s_{2.262}], ([0.230, 0.365], [0.420, 0.545], [0.420, 0.545])) \rangle)$$

$$Y^- = (\langle ([s_{1.131}, s_{1.508}], ([0.126, 0.230], [0.545, 0.635], [0.635, 0.708])) \rangle, \langle ([s_{0.735}, s_{0.98}], ([0.117, 0.201], [0.569, 0.745], [0.745, 0.799])) \rangle, \langle ([s_{1.508}, s_{1.508}], ([0.081, 0.126], [0.545, 0.635], [0.770, 0.825])) \rangle)$$

**Step 5: Obtain the distance between each alternative and the positive ideal solution, and between each alternative and the negative ideal solution, by formulas (22)-(23), we can get**

$$D^+ = (0.402, 0.065, 0.089, 0.066)$$

$$D^- = (0.052, 0.073, 0.080, 0.065)$$

**Step 6: Calculate the closeness coefficients of each alternative to the ideal solution, by formula (24) and then we can get**

$$cc_i = (0.885, 0.472, 0.527, 0.503)$$

**Step 7: Rank the alternatives**

According to the closeness coefficient above, we can choose an alternative with minimum to  $cc_i$  in ascending order. We can get

$$A_2 \geq A_4 \geq A_3 \geq A_1$$

So, the most desirable alternative is  $A_2$

**V-Comparison analysis with the existing interval neutrosophic uncertain linguistic multicriteria decision making method.**

Recently, J. Ye [20] developed a new method for solving the MCDM problems with interval neutrosophic uncertain linguistic information. In this section, we will perform a

comparison analysis between our new method and the existing method, and then highlight the advantages of the new method over the existing method.

(1) Compared with method proposed proposed by J. Ye [20], the method in this paper can solve the MADM problems with unknown weight, and rank the alternatives by the closeness coefficients. However, the method proposed by J. Ye [20] cannot deal with the unknown weight It can be seen that the result of the proposed method is same to the method proposed in [20].

(2) Compared with other extended TOPSIS method Because the interval neutrosophic uncertain linguistic variables are the generalization of interval neutrosophic linguistic variables (INLV), interval neutrosophic variables (INV),and intuitionistic uncertain linguistic variable. Obviously, the extended TOPSIS method proposed by J. Ye [19], Z. Wei [54], Z. Zhang and C. Wu [3], are the special cases of the proposed method in this paper. In a word, the method proposed in this paper is more generalized. At the same time, it is also simple and easy to use.

**VI-Conclusion**

In real decision making, there is great deal of qualitative information which can be expressed by uncertain linguistic variables. The interval neutrosophic uncertain linguistic variables were produced by combining the uncertain linguistic variables and interval neutrosophic set, and could easily express the indeterminate and inconsistent information in real world. TOPSIS had been proved to be a very effective decision making method and has been achieved more and more extensive applications. However, the standard TOPSIS method can only process the real numbers. In this paper, we extended TOPSIS method to deal with the interval neutrosophic uncertain linguistic variables information, and proposed an extended TOPSIS method with respect to the MADM problems in which the attribute values take the form of the interval neutrosophic and attribute weight unknown. Firstly, the operational rules

and properties for the interval neutrosophic uncertain linguistic variables were presented. Then the distance between two interval neutrosophic uncertain linguistic variables was proposed and the attribute weight was calculated by the maximizing deviation method, and the closeness coefficient to the ideal solution for each alternative used to rank the alternatives. Finally, an illustrative example was given to illustrate the decision making steps, and compared with the existing method and proved the effectiveness of the proposed method. However, we hope that the concept presented here will create new avenue of research in current neutrosophic decision making area.

## References

- [1] A. Kharal, A Neutrosophic Multicriteria Decision Making Method, New Mathematics and Natural Computation, Creighton University, USA, 2013.
- [2] A.Q. Ansaria, R. Biswas and S. Aggarwal, Neutrosophic classifier: An extension of fuzzy classifier, Applied Soft Computing 13 (2013) 563-573.
- [3] C.L. Hwang, K. S. Yoon, Multiple attribute decision making: Methods and applications, Berlin: Springer-verlag, 1984.
- [4] D. Rabounski, F. Smarandache, L. Borissova, Neutrosophic Methods in General Relativity, Hexis, (2005).
- [5] G. Lee, K. S. Jun, E. S. Chung, "Robust spatial flood vulnerability assessment for han river using TOPSIS with  $\alpha$  -cut level set", Expert Systems with Applications, vol.41,no2,(2014)644-654.
- [6] F. G. Lupiáñez, On neutrosophic topology, Kybernetes, 37/6, (2008) 797-800.
- [7] F. Smarandache, A Unifying Field in Logics. Neutrosophy: Neutrosophic Probability, Set and Logic. Rehoboth: American Research Press, (1998).
- [8] H. Wang, F. Smarandache, Y. Zhang, and R. Sunderraman, Single valued Neutrosophic Sets, Multispace and Multistructure 4 (2010) 410-413.
- [9] H. Wang, F. Smarandache, Y. Zhang, and R. Sunderraman, Interval Neutrosophic Sets and Logic: Theory and Applications in Computing, Hexis, Phoenix, AZ, (2005).
- [10] I. Deli and S. Broumi, Neutrosophic multisets and its application in medical diagnosis, 2014, (submitted)
- [11] I. Deli, Interval-valued neutrosophic soft sets and its decision making <http://arxiv.org/abs/1402.3130>.
- [12] I. Deli, S. Broumi, Neutrosophic soft sets and neutrosophic soft matrices based on decision making, <http://arxiv:1404.0673>.
- [13] I. Deli, Y. Toktas, S. Broumi, Neutrosophic Parameterized Soft relations and Their Application, Neutrosophic Sets and Systems, Vol. 4, (2014) 25-34
- [14] J. Ye, Similarity measure between interval neutrosophic sets and their applications in multicriteria decision making journal of intelligent and fuzzy systems 26,(2014) 165-172.
- [15] J. Ye, Multiple attribute group decision -making method with completely unknown weights based on similarity measures under single valued neutrosophic environment, journal of intelligent and Fuzzysystems,2014,DOI:10.3233/IFS-141252.
- [16] J. Ye, single valued neutrosophic cross-entropy for multicriteria decision making problems, Applied Mathematical Modelling,38, (2014) 1170-1175.
- [17] J. Ye, single valued neutrosophic minimum spanning tree and it clustering method, Journal of intelligent Systems 23(3), (2014)311-324.
- [18] J. Ye, Multicriteria decision-making method using the correlation coefficient under single-valued neutrosophic environment. International Journal of General Systems, Vol. 42, No. 4,(2013) 386-394, <http://dx.doi.org/10.1080/03081079.2012.761609>.
- [19] J. Ye, Some aggregation operators of interval neutrosophic linguistic numbers for multiple attribute decision making, Journal of Intelligent and Fuzzy System (2014) -, DOI:10.3233/IFS-141187
- [20] J. Ye, Multiple attribute decision making based on interval neutrosophic uncertain linguistic variables, Neural Computing and Applications,2014,(submitted)
- [21] J. Ye, A Multicriteria decision-making method using aggregation operators for simplified neutrosophic sets,Journal of Intelligent and Fuzzy System (2013) -, DOI:10.3233/IFS-130916.
- [22] K. Atanassov, More on intuitionistic fuzzy sets, Fuzzy Sets and Systems Vol 33,no.5,(1989) 37-46.
- [23] K. Atanassov, Gargov, interval -valued intuitionistic fuzzy sets, Fuzzy Sets and Systems 31 (1989) 343-349.
- [24] K. Atanassov, Operators over interval -valued intuitionistic fuzzy sets, Fuzzy Sets and Systems 64 (1994) 159-174.
- [25] L.A. Zadeh, Fuzzy sets, Information and control, Vol8 (1965) 338-356.
- [26] L. Zeng, Expected value method for fuzzy multiple attribute decision making, Tsinghua Science and Technology,11,(2006) 102-106.
- [27] L. Peide, Y. Li, Y. Chen, Some Generalized Neutrosophic number Hamacher Aggregation Operators and Their Application to Group Decision Making, International Journal of Fuzzy Systems, Vol,16,No.2,(2014) 212-255.
- [28] M. Arora, R. Biswas and U.S. Pandey, Neutrosophic Relational Database Decomposition, International Journal of Advanced Computer Science and Applications, 2(8) (2011) 121-125.
- [29] M. Arora and R. Biswas, Deployment of Neutrosophic Technology to Retrieve Answers for Queries Posed in Natural Language, in 3rdInternational Conference on Computer Science and Information Technology, (2010) 435-439.
- [30] P. Chi, L. Peid, An Extended TOPSIS Method for the Multiple Attribute Decision Making Problems Based on Interval Neutrosophic, Neutrosophic Sets and Systems, 1 (2013) 63-70.
- [31] P. Liu, Y. Wang, Multiple attribute decision-making method based on single-valued neutrosophic normalized weighted Bonferroni mean, Neural Computing and Applications,2014
- [32] P. Biswas, S.Paramanik, B. C. Giri, A New Methodology for neutrosophic Multi-attribute Decision Making with unknown weight Information, Neutrosophic Sets and Systems, Vol 3,(2014) 44-54.
- [33] P. K. Maji, Neutrosophic Soft Set, Annals of Fuzzy Mathematics and Informatics, Vol 5, No. 1, ISSN:2093-9310, ISSN: 2287-623.
- [34] P.D. Liu, Y. Su, "The extended TOPSIS based on trapezoid fuzzy linguistic variables», Journal of Convergence Information Technology, Vol.5,No.4,(2010) 38-53.
- [35] R. Sahin and A. Kucuk, Generalized Neutrosophic Soft Set and its Integration to Decision Making Problem, Appl. Math. Inf. Sci. 8(6) (2014) 2751-2759

- [36] R. Şahin and A. Küçük, On Similarity and Entropy of Neutrosophic Soft Sets, Journal of Intelligent and Fuzzy 17 Systems, DOI: 10.3233/IFS-141211.
- [37] S. Aggarwal, R. Biswas and A. Q. Ansari, Neutrosophic Modeling and Control, Computer and Communication Technology (2010) 718-723.
- [38] S. Broumi and F. Smarandache, Intuitionistic Neutrosophic Soft Set, Journal of Information and Computing Science, England, UK, 8(2) (2013) 130-140.
- [39] S. Broumi, Generalized Neutrosophic Soft Set, International Journal of Computer Science, Engineering and Information Technology, 3(2) (2013) 17-30.
- [40] S. Broumi, F. Smarandache, Correlation Coefficient of Interval Neutrosophic set, Periodical of Applied Mechanics and Materials, Vol. 436, 2013, with the title Engineering Decisions and Scientific Research in Aerospace, Robotics, Biomechanics, Mechanical Engineering and Manufacturing; Proceedings of the International Conference ICAMERA, Bucharest, October 2013.
- [41] S. Broumi, F. Smarandache, Several Similarity Measures of Neutrosophic Sets, Neutrosophic Sets and Systems, 1, (2013) 54-62.
- [42] S. Broumi, I. Deli, and F. Smarandache, Relations on Interval Valued Neutrosophic Soft Sets, Journal of New Results in Science, 5 (2014) 1-20
- [43] S. Broumi, F. Smarandache, More on Intuitionistic Neutrosophic Soft Sets, Computer Science and Information Technology 1(4)(2013) 257-268, DOI: 10.13189/csit.2013.010404.
- [44] S. Broumi, I. Deli, F. Smarandache, Neutrosophic Parametrized Soft Set theory and its decision making problem, Italian journal of pure and applied mathematics N. 32, (2014) 1 -12.
- [45] S. Broumi, F. Smarandache, On Neutrosophic Implications, Neutrosophic Sets and Systems, Vol. 2, (2014) 9-17.
- [46] S. Broumi, F. Smarandache, "Rough neutrosophic sets. Italian journal of pure and applied mathematics, N.32, (2014) 493-502.
- [47] S. Broumi, R. Sahin, F. Smarandache, Generalized Interval Neutrosophic Soft Set and its Decision Making Problem, Journal of New Results in Science No 7, (2014)29-47.
- [48] S. Broumi, F. Smarandache, P. K.Maji, Intuitionistic Neutrosophic Soft Set over Rings, Mathematics and Statistics 2(3): (2014) 120-126, DOI: 10.13189/ms.2014.020303.
- [49] Y. Q. Wei and P.D. Liu, "Risk Evaluation Method of High-technology Based on Uncertain Linguistic Variable and TOPSIS Method", Journal of Computers, Vol.4, No.3, (2009)276-282.
- [50] Z. P. Chen, W. Yang A new multiple attribute group decision making method in intuitionistic fuzzy setting, Applied Mathematical Modelling, Vol.355, (2011) 4424-4437.
- [51] Z. Xu, A method based on distance measure for interval –valued intuitionistic fuzzy group decision making, information Science, 180 (2010)181-190.
- [52] Z. Xu, An approach based on similarity measure to multiple attribute decision making with trapezoid fuzzy linguistic variables, Springer, Berlin, Heidelberg, (2005)110-117
- [53] Z. Zhang, C. Wu, A novel method for single –valued neutrosophic multicriteria decision making with incomplete weight information, Neutrosophic Sets and Systems, Vol 4, 2014 (35-49).
- [54] Z. Wei, An extended TOPSIS method for multiple attribute decision Making Based on Intuitionistic Uncertain Linguistic Variables, Engineering Letters, 22:3, EL\_22-3-04.
- [55] Z. Yue, "An Extended TOPSIS for determining weight of decision makers with interval numbers", Knowledge-Based System, Vol.24, No.1, (2014) 14-153.

Received: January 16, 2015. Accepted: March 14, 2015