

7-29-2023

## Selecting the Suitable Waste to Energy Technology for India Using MULTIMOORA Method under Pythagorean Neutrosophic Fuzzy Logic

R. Narmada Devi

S. Sowmiya

A. Anuja

Follow this and additional works at: [https://digitalrepository.unm.edu/nss\\_journal](https://digitalrepository.unm.edu/nss_journal)

---

### Recommended Citation

Devi, R. Narmada; S. Sowmiya; and A. Anuja. "Selecting the Suitable Waste to Energy Technology for India Using MULTIMOORA Method under Pythagorean Neutrosophic Fuzzy Logic." *Neutrosophic Sets and Systems* 56, 1 (2023). [https://digitalrepository.unm.edu/nss\\_journal/vol56/iss1/19](https://digitalrepository.unm.edu/nss_journal/vol56/iss1/19)

This Article is brought to you for free and open access by UNM Digital Repository. It has been accepted for inclusion in *Neutrosophic Sets and Systems* by an authorized editor of UNM Digital Repository. For more information, please contact [disc@unm.edu](mailto:disc@unm.edu).



# Selecting the Suitable Waste to Energy Technology for India Using MULTIMOORA Method under Pythagorean Neutrosophic Fuzzy Logic

R.Narmada Devi<sup>1</sup>, S.Sowmiya<sup>2</sup>, A.Anuja<sup>3</sup>

<sup>1</sup>Associate Professor, Department of Mathematics, Vel Tech Rangarajan Dr.Sanguthala R&D Institute of Science and Technology, Chennai, Tamil Nadu, India; drnarmadadevi@veltech.edu.in

<sup>2</sup>Research Scholar, Department of Mathematics, Vel Tech Rangarajan Dr.Sanguthala R&D Institute of Science and Technology, Chennai, Tamil Nadu, India; sowmiyamathematics123@gmail.com

<sup>3</sup>Assistant Professor, Department of Mathematics, Arulmigu Palaniandavar Arts College for Women, Dindigul, Tamil Nadu, India; anujaphd22@gmail.com

**Abstract.** Municipal solid waste (MSW) development has increased on a global scale, posing significant socio-economic and environmental challenges. Waste to energy conversion is strategic because it can determine the best waste-to-energy technology. Recognizing the significance of waste in energy selection, this research aims to select the best technology based on its eco-friendliness. A two-phase methodology is used for presenting a framework for waste to energy technology selection. The first phase involves the selection of criteria for this problem and the perspectives of decision makers. Ranking the selected criteria using a novel SWARA method, and ranking the technology of WtE with respect to selected criteria weights are obtained. In this paper, we investigate the WtE technology problem using the novel concept of the Pythagorean Neutrosophic fuzzy set (PNFS). This set is a hybrid of the Pythagorean and Neutrosophic fuzzy sets. In this paper, we propose the best WtE technology for India. We employ the MULTIMOORA method in the Pythagorean Neutrosophic fuzzy environment for this purpose. Sensitivity and comparison analyses are also performed to ensure the framework's robustness. The findings of this study are useful in ranking the technology, and as a result, waste management can replicate the proposed framework for waste disposal for their new platform.

**Keywords:** Pythagorean Fuzzy Set, Neutrosophic Fuzzy Set, Pythagorean Neutrosophic Fuzzy Set, Multi-Criteria Decision Making, MULTIMOORA, WtE Technology.

## 1. Introduction

Real-world decision-making problems are typically so complex and organized that traditional decision-making techniques cannot be applied. Human decisions are represented as precise numbers in traditional decision-making techniques. In many real applications, however, the information may be incomplete, or the experts may be unable to assign precise statistical measures to the assessment. As some of the judging criteria are subjective and descriptive in

nature, it is challenging for the decision maker to express his or her priorities using precise statistical measures [1]. Rather, decision-makers generally focus on making linguistic assessment processes in the decision matrix. Moreover, conventional decision-making strategies are far less capable of coping with the imprecise or ambiguous nature of linguistic evaluations [2].

The increasing industrialization, urbanisation, and changes in lifestyle that accompany the process of economic growth result in the generation of increasing amounts of waste, posing increased environmental threats. In recent years, technologies have been developed that not only aid in the generation of a significant amount of distributed energy but also in the reduction of waste for safe disposal. The Ministry is promoting all available technology options for establishing projects for the recovery of energy in the form of biogas, bio-CNG, and electricity from renewable agricultural, industrial, and urban wastes, such as municipal solid wastes, vegetable and other market wastes, slaughterhouse waste, agricultural residues, and industrial wastes and effluents [3].

Solid waste management (SWM) disposal is at an advanced stage in India. There is an imperative need to build facilities to treat and dispose of growing amounts of MSW. More than 90% of waste in India is thought to be dumped in an unsatisfactory fashion. Waste dumps are estimated to have occupied approximately  $1400 \text{ km}^2$  in the past few years, and this figure is expected to rise in the future. Waste disposal that is properly engineered protects public health and preserves critical environmental resources such as groundwater, surface water, soil fertility, and air quality [4]. Globally, solid waste generation is steadily increasing. According to the World Bank [15], worldwide annual waste generation has been rapidly increasing. This significant increase in MSW generation is affected by a variety of factors like economic growth, rising population, technological growth, urban growth, and rural-to-urban migration, among others. Along with the increasing quantity of waste, the concentration of MSW is becoming more diverse and complicated as a result of the development of developing societies based on consumer-based lifestyles [15,16]. There is an urgent need to develop WtE technology, which can significantly reduce waste while also protecting the environment and public health.

Real-world problems, such as decision-making problems, are complicated and involve ambiguity and fuzzy logic. This motivated Zadeh [5,6] to develop fuzzy set theory as a means to describe and transform information that was not accurate, but rather imprecise. Fuzzy logic theory provides a mathematical foundation for capturing the uncertainty and risk related to human thought processes such as logic and understanding [7]. Because of the complexity of information and the ambiguity of the human mind, the membership function of the fuzzy set is not always sufficient to reveal the characteristics of things. To address this limitation of the fuzzy set, Atanassov [8] transformed it into an intuitionistic fuzzy set (IFS) by including a non-membership function and a hesitancy function. An IFS can describe things in three

ways: superiority, inferiority, and hesitation, which are typically represented by intuitionistic fuzzy numbers (IFNs) [9]. Yager [10–12] recently proposed the concept of Pythagorean fuzzy set (PFS) as a different assessment feature to obtain more valuable information under imprecise and ambiguous environments, which is characterised by the membership and non-membership degree satisfying the condition that their square sum is not greater than 1. Zhang and Xu [13] developed the Pythagorean fuzzy number concept and provided a comprehensive computational model for PFS.

In 1998, Smarandache [14] proposed the concept of Neutrosophic set and Neutrosophic probability, as well as their logic, which has three distinct logic components: truthfulness, indeterminacy, and falsity. This concept also includes the concept of hesitation, which gives the research a significant impact in various research areas. In a Neutrosophic fuzzy set, truth membership is denoted by  $T$ , indeterminacy membership by  $I$ , and falsity membership by  $F$ . These are all independent, with a sum of  $0 \leq T + I + F \leq 3$ , while uncertainty in IFS is determined by the degree of membership and non-membership, the indeterminacy factor in Neutrosophic fuzzy sets is independent of the truth and falsity values. The uncertainty, falsity, and hesitation information of a real-life problem can be described using a Neutrosophic fuzzy number. In this paper, we use the proposed method to combine two sets, such as Pythagorean and Neutrosophic fuzzy sets, to provide a more reliable solution to the WtE problem. In addition, many researchers studied the WtE problem using various types of fuzzy sets in various MCDM methods.

Several studies have been conducted to propose criteria for selecting waste-to-energy technologies. Abdel-Basset et al. [17] proposed and defined some operational rules for an advanced type of Neutrosophic technique in a type 2 environment. Farooq et al. presented appropriate MSW waste-to-energy technologies [18]. Yap and Nixon [19] used multi-criteria decision making based on the analytical hierarchical process to evaluate and compare WtE technologies. Different types of waste to energy technology for MSW were evaluated by Atwadkar et al [20] for Kolhapur. A life cycle assessment (LCA) of WtE treatment plants for electricity generation was proposed by Ayodele [21]. Abdel-Basset et al. [22] discussed the creation of an evaluation strategy to help Egypt choose the best renewable energy sources. Beyene et al. [23] discussed the most recent updates on WtE technologies, which convert waste into electricity, hydrogen gas, and other chemical feedstocks while being environmentally friendly. Chiu et al. [24] investigated the feasibility of using microbial fuel cells to convert solid waste organics into energy under a variety of operational conditions. To locate sustainable photovoltaic farms, Abdel-Basset et al. [25] used a hybrid multi-criteria decision-making approach in a neutrosophic environment. Khan et al. [26] explored the effects of renewable electricity generation from waste. Kurbatova and Abu-Qdais [27] used AHP to evaluate various WtE

options in order to select the most appropriate technology for the Moscow region. Malav et al. [28] discussed the difficulties associated with WtE projects in India. Reddy [29] examined MSW WtE conversion in India. Abdel-Basset et al. [30] evaluated the sustainable bioenergy production through a case study in Egypt and further suggested that converting municipal wastes to biogas is the most suitable sustainable bioenergy technology.

Different WtE technologies were reviewed by many researchers. All of the studies reviewed were aimed at identifying the most feasible WtE options for various countries using MCDM methods that are rapidly developing waste management. As a result, the aim of the research was to create a general framework for selecting the most appropriate WtE technologies for India based on environmental, socioeconomic, and technological factors. To achieve this, we employ the MULTIMOORA method, which employs a Pythagorean Neutrosophic fuzzy set to select the best solution.

## 2. Preliminaries

**Definition 2.1.** [31–33] Let  $U$  be a universal set. Then, a Pythagorean fuzzy set  $P$ , which is a set of ordered pairs over  $U$ , is defined by the following:

$$P = \{(u, \phi(u), \gamma(u)) | u \in U\}$$

where  $\phi_P(u) : U \rightarrow [0, 1]$  and  $\gamma_P(u) : U \rightarrow [0, 1]$  define the degree of membership and the degree of non-membership, respectively, of the element  $u \in U$  to  $P$ , which is a subset of  $U$ , and for every  $u \in U$ :

$$0 \leq (\phi_P(u))^2 + (\gamma_P(u))^2 \leq 1$$

Suppose  $(\phi_P(u))^2 + (\gamma_P(u))^2 \leq 1$  then there is a degree of indeterminacy of  $u \in U$  to  $P$  defined by  $\pi_P(u) = \sqrt{1 - [(\phi_P(u))^2 + (\gamma_P(u))^2]}$  and  $\pi_P(u) \in [0, 1]$ . In what follows,  $(\phi_P(u))^2 + (\gamma_P(u))^2 + (\pi_P(u))^2 = 1$ . Otherwise,  $\pi_P(u) = 0$  whenever  $(\phi_P(u))^2 + (\gamma_P(u))^2 = 1$ .

**Definition 2.2.** [31–33]

Let  $U$  be a universal set. A Neutrosophic fuzzy set  $N$  on  $U$  is an object of the form:

$$N = \{(u, \phi_N(u), \Omega_N(u), \gamma_N(u)) : u \in U\}$$

where  $\phi_N(u), \Omega_N(u), \gamma_N(u) \in [0, 1], 0 \leq \phi_N(u) + \Omega_N(u) + \gamma_N(u) \leq 3$  for all  $u \in U$ ,  $\phi_N(u)$  is the degree of membership,  $\Omega_N(u)$  is the degree of indeterminacy and  $\gamma_N(u)$  is the degree of non-membership. Here,  $\phi_N(u)$  and  $\gamma_N(u)$  are dependent component and  $\Omega_N(u)$  is an independent components.

**Definition 2.3.** [31–33] Let  $U$  be a universal set. A Pythagorean Neutrosophic fuzzy set (PNFS) with  $T$  and  $F$  are dependent Neutrosophic components  $D$  on  $U$  is an object of the

TABLE 1. Pythagorean Neutrosophic fuzzy linguistic scale

| Linguistic term     | membership values | indeterminacy values | non-membership values |
|---------------------|-------------------|----------------------|-----------------------|
| Extremely high (EH) | 0.85              | 0.10                 | 0.15                  |
| Very high (VH)      | 0.75              | 0.20                 | 0.25                  |
| Medium High (MH)    | 0.65              | 0.30                 | 0.35                  |
| Medium (M)          | 0.55              | 0.40                 | 0.45                  |
| Medium Low (ML)     | 0.35              | 0.60                 | 0.65                  |
| Very Low (VL)       | 0.25              | 0.70                 | 0.75                  |
| Extremely Low (EL)  | 0.15              | 0.80                 | 0.85                  |

form

$$D = \{ (u, \phi_N(u), \Omega_N(u), \gamma_N(u)) : u \in U \}$$

where  $\phi_N(u), \Omega_N(u), \gamma_N(u) \in [0, 1]$ ,  $0 \leq (\phi_N(u))^2 + (\Omega_N(u))^2 + (\gamma_N(u))^2 \leq 2$ , for all  $u \in U$ ,  $\phi_N(u)$  is the degree of membership,  $\Omega_N(u)$  is the degree of indeterminacy and  $\gamma_N(u)$  is the degree of non-membership. Here,  $\phi_N(u)$  and  $\gamma_N(u)$  are dependent component and  $\Omega_N(u)$  is an independent components.

**Definition 2.4.** [32] The score function of the Pythagorean Neutrosophic fuzzy sets with dependent Pythagorean Neutrosophic components  $I$  and  $F$  are defined as:

$$S_D(u) = (T + (1 - I) + (1 - F))$$

with the condition  $0 \leq (\phi_N(u))^2 + (\Omega_N(u))^2 + (\gamma_N(u))^2 \leq 2$ .

**Definition 2.5.** Linguistic variable deals with many real-world decision-making problems which are more complex and uncertain. Many research studies have different linguistic variables with fuzzy numbers [34]. Here, the linguistic variables with Pythagorean Neutrosophic fuzzy number to evaluate the WtE technologies based on selected criteria and the linguistic scale is presented in Table 1.

### 3. Mathematical Methods

MULTIMOORA is one of the most proficient MCDM models that emerged from the important contributions of Brauers and Zavadskas [35]. The MOORA method is the ancestor of the MULTIMOORA method. It employs three methods: the ration system (RS), the reference point (RP), and the full multiplicative form (FMF). The MULTIMOORA method algorithm is as follows: [34, 36]

### 3.1. Ration system approach:

The overall significance of the  $i^{th}$  alternative is as follows:

$$X_i = x_i^+ - x_i^- \quad (1)$$

where

$$x_i^+ = \sum_{j \in B} a_{ij} \quad (2)$$

$$x_i^- = \sum_{j \in C} a_{ij} \quad (3)$$

where,  $x_i^+$  and  $x_i^-$  denote the sum of the normalized performance ratings of the importances obtained on the basis of the benefit and cost criteria;  $a_{ij}$  denotes the normalized performance ratings. Here, B and C represents the benefit and cost criterion respectively;  $i = 1, 2, 3, \dots, s$  and  $j = 1, 2, 3, \dots, t$ .

The normalized performance ratings are obtained as:

$$a_{ij} = \frac{x_{ij}}{\sqrt{\sum_{i=1}^x (x_{ij})^2}}$$

where  $x_{ij}$  is the performance rating of the  $i^{th}$  alternative to the  $j^{th}$  criterion. The compared alternatives are ranked in descending order based on their  $x_i$  values, with the alternative with the highest  $x_i$  value being the best ranked.

### 3.2. The reference point approach:

The optimization based on the reference point can be shown as below:

$$R_i = \min_i (\max_j W_j \times d(p_j - a_{ij})) \quad (4)$$

Here,  $R_i$  is the overall performance of the reference point approach and  $d(p_j - a_{ij})$  is the distance between the reference point and the normalized matrix, which is multiplied by the criteria weights. Here,  $p_j$  represents the  $j^{th}$  coordinate of the reference point, as:

$$\begin{aligned} p_j &= \max_i a_{ij}; j \in B \\ p_j &= \min_i a_{ij}; j \in C \end{aligned} \quad (5)$$

The compared alternatives are ranked in ascending order based on their  $r_i$  values, and the alternative with the lowest value of  $r_i$  is the best ranked.

### 3.3. Full multiplicative form:

In this approach, the overall utility of the alternative can be calculated as follows:

$$F_i = \frac{B_i}{C_i} \quad (6)$$

where  $B_i$  is the product of the weighted performance ratings of the benefit criteria and  $C_i$  is the product of the weighted performance ratings of the alternative's cost criteria. The compared alternatives are ranked in descending order and the highest value of  $F_i$  is the best result.

The MULTIMOORA was used to determine the final ranking of alternatives. Generally, different parts of the MULTIMOORA approach provide different ranking orders. The dominance theory was proposed by Brauers and Zavadskas [37] in order to describe the ranks provided by three approaches of the MULTIMOORA and determine the final ranking values.

### 3.4. SWARA weighting method

Kresuliene et al. [38] propose the SWARA method, which assists experts in determining criteria weights. The SWARA method is described below: [34]

**Step 1:** Rank the criteria based on their importance.

**Step 2:** Determine its relative importance  $\beta_i$ .

**Step 3:** To calculate the coefficient value  $\Gamma_j$ , where  $\Gamma_j = \beta_j + 1$ .

**Step 4:** Calculate the initial weights  $\omega_j$ ,  $\omega_j = \frac{\beta_j - 1}{\beta}$ .

**Step 5:** Obtain the final weight of the criteria  $W_j$ , where  $W_j = \frac{\omega_j}{\sum \omega_j}$ .

## 4. Application

Nowadays, the amount of waste is rapidly increasing day by day due to population growth and a wide range of technologies. The government authorities are implementing different kinds of disposal methods to reduce the waste, but they are still finding the best solution for this problem without any harmful impact on the environment and society. In the current situation, waste management is facing many difficulties in reducing the waste that comes from industries, houses, institutes, hospitals, etc. Therefore, we make it necessary to reduce the waste in a good manner and we make energy from that waste. Developing countries are focusing on advanced technologies to make energy from MSW wastes, which helps to find environmentally friendly energy while at the same time reducing the amount of waste. In this study, we proposed the MULTIMOORA method to obtain the best WtE technologies for India using a Pythagorean Neutrosophic fuzzy set. For this, we chose four types of WtE technologies based on economic, environmental, social, and technology aspects.



TABLE 2. Weight values of the criteria

| Criteria    | $\beta_j$ | $\Gamma_j = \beta_j + 1$ | $\omega_j = \frac{\beta_j - 1}{\beta}$ | $W_j = \frac{\omega_j}{\sum \omega_j}$ |
|-------------|-----------|--------------------------|--|--|
| Technology  | 0         | 1                        | 1                                      | 0.392                                  |
| Society     | 0.25      | 1.25                     | 0.8                                    | 0.314                                  |
| Environment | 0.35      | 1.6                      | 0.5                                    | 0.196                                  |
| Economic    | 0.4       | 2                        | 0.25                                   | 0.098                                  |

## 5. Numerical example

In this section, we discuss the WtE technology problem under the Pythagorean Neutrosophic fuzzy set using the MULTIMOORA method. Here, the experts evaluate this problem based on the selected criteria. The WtE technologies are  $M_1$  – chemical and mechanical methods;  $M_2$  – new trends in WtE;  $M_3$  – biochemical methods; and  $M_4$  – thermal conversion method. To solve this problem, experts evaluate the WtE technologies using the proposed method. The linguistic scale is used to form a decision matrix. We are now analyzing the problem using the suggested model.

### 5.1. SWARA method:

Using the SWARA method, we obtain the weight values of the criteria, which are shown in Table 2.

### 5.2. MULTIMOORA method:

The WtE technologies and the criteria are given below:

$M_1$  – Chemical and mechanical method

$M_2$  – New trends in WtE method

$M_3$  – Biochemical method

$M_4$  – Thermal conversion method

TABLE 3. The ratings of the WtE technology obtained from the expert

| Criteria / WtE | $C_1$              | $C_2$              | $C_3$              | $C_4$              |
|----------------|--------------------|--------------------|--------------------|--------------------|
| $M_1$          | (0.75, 0.40, 0.45) | (0.25, 0.70, 0.45) | (0.15, 0.30, 0.15) | (0.85, 0.70, 0.45) |
| $M_2$          | (0.85, 0.40, 0.35) | (0.55, 0.80, 0.25) | (0.35, 0.20, 0.75) | (0.85, 0.60, 0.45) |
| $M_3$          | (0.55, 0.20, 0.35) | (0.25, 0.40, 0.65) | (0.75, 0.70, 0.65) | (0.85, 0.20, 0.65) |
| $M_4$          | (0.85, 0.30, 0.65) | (0.85, 0.60, 0.75) | (0.85, 0.30, 0.65) | (0.15, 0.40, 0.65) |

TABLE 4. Decision matrix

|       | $C_1$ | $C_2$ | $C_3$ | $C_4$ |
|-------|-------|-------|-------|-------|
| $M_1$ | 1.9   | 1.1   | 1.7   | 1.7   |
| $M_2$ | 2.1   | 1.5   | 1.4   | 1.8   |
| $M_3$ | 2.0   | 1.2   | 1.4   | 2.1   |
| $M_4$ | 1.9   | 1.5   | 1.9   | 1.1   |

$C_1$  – Economic

$C_2$  – Society

$C_3$  – Environment

$C_4$  – Technology

(7)

The experts then assess the WtE technology using the evaluation criteria they have chosen. Table 3 shows the expert evaluation results and which shows the ratings in the form of the PNFNs obtained as the result of the transformation of the linguistic variables from Table 1.

5.3. *Ratio system approach:*

The ranking results and the ranking order of the WtE technology were obtained on the basis of the RS approach. Using the PNFSS score function to create the decision matrix shown in Table 4, by applying Eqs. (2) and (3), we calculate the normalized decision matrix, which is shown in Table 5. The final ranking result of the RS approach is given in Table 6 using Eq. (1).

5.4. *Reference point approach*

By applying the procedure of RP, we obtained the weighted distance between the reference point and the normalized decision matrix using Eqs. (4), it is presented in Table 7. The reference point is calculated by applying Eq.(5) which are (0.4805, 0.5609, 0.5885, 0.5939) and the final ranking results are given in Table 8.

TABLE 5. Normalized decision matrix

|       | $C_1$  | $C_2$  | $C_3$  | $C_4$  |
|-------|--------|--------|--------|--------|
| $M_1$ | 0.4805 | 0.4113 | 0.5266 | 0.5048 |
| $M_2$ | 0.5311 | 0.5609 | 0.4337 | 0.5345 |
| $M_3$ | 0.5058 | 0.4487 | 0.4337 | 0.5939 |
| $M_4$ | 0.4805 | 0.5609 | 0.5885 | 0.3266 |

TABLE 6. The final ranking results for RS

| WtE   | Ranking values | Rank |
|-------|----------------|------|
| $M_1$ | 0.9622         | 4    |
| $M_2$ | 0.998          | 1    |
| $M_3$ | 0.9705         | 3    |
| $M_4$ | 0.9955         | 2    |

TABLE 7. Weighted distance between reference point and the normalized matrix

|       | $C_1$   | $C_2$  | $C_3$  | $C_4$  |
|-------|---------|--------|--------|--------|
| $M_1$ | 0       | 0.0469 | 0.0121 | 0.0349 |
| $M_2$ | -0.0049 | 0      | 0.0303 | 0.0232 |
| $M_3$ | -0.0024 | 0.0352 | 0.0303 | 0      |
| $M_4$ | 0       | 0      | 0      | 0.1047 |

TABLE 8. The final ranking results for RP

| WtE   | Ranking values | Rank |
|-------|----------------|------|
| $M_1$ | 0.0469         | 3    |
| $M_2$ | 0.0303         | 1    |
| $M_3$ | 0.0352         | 2    |
| $M_4$ | 0.1047         | 4    |

5.5. Full multiplicative form:

The ranking results and the ranking order of the WtE technology obtained on the basis of the FMF approach, by applying Eq (6), are shown in Table 10. For this, we first obtained the weighted normalized matrix, which is given in Table 9. The final ranking results are obtained using dominance theory, it as presented in Table 11.

TABLE 9. Weighted normalized decision matrix

|       | $C_1$   | $C_2$  | $C_3$  | $C_4$  |
|-------|---------|--------|--------|--------|
| $M_1$ | 0.0470  | 0.1291 | 0.1032 | 0.1978 |
| $M_2$ | -0.0520 | 0.1761 | 0.0850 | 0.2095 |
| $M_3$ | -0.0495 | 0.1408 | 0.0850 | 0.2328 |
| $M_4$ | 0.0470  | 0.1761 | 0.1153 | 0.1280 |

TABLE 10. The final ranking results for FMF

| WtE   | Ranking values | Rank |
|-------|----------------|------|
| $M_1$ | 0.0560         | 2    |
| $M_2$ | 0.0596         | 1    |
| $M_3$ | 0.0545         | 3    |
| $M_4$ | 0.0495         | 4    |

TABLE 11. The final ranking results of MULTIMOORA method

| WtE   | RA | RP | FMF | Final rank |
|-------|----|----|-----|------------|
| $M_1$ | 4  | 3  | 2   | 2          |
| $M_2$ | 1  | 1  | 1   | 1          |
| $M_3$ | 3  | 2  | 3   | 3          |
| $M_4$ | 2  | 4  | 4   | 4          |

From this Table 11,  $M_2$ – New trends in WtE technology is the most suitable and environment friendly method to convert the waste into energy.

## 6. Comparison and sensitivity analysis

### 6.1. Comparison Analysis

This section compares the proposed approach to a number of existing methods from the literature in order to demonstrate the method’s efficiency and performance in comparison to those methods. The proposed methodology was compared to two existing techniques: the VIKOR [39] and the MOORA model [40]. These MCDM methods use the proposed criterion weights. The results of the ranking order comparison are shown in Table 12. The proposed ranking yields different results than the existing VIKOR and MOORA models. As a result, when compared to other MCDM models, the proposed approach yields more reliable findings.

TABLE 12. Comparison analysis results

| WtE   | VIKOR  | Rank | MOORA  | Rank | Proposed method |
|-------|--------|------|--------|------|-----------------|
| $M_1$ | 0.8010 | 4    | 0.3651 | 4    | 3               |
| $M_2$ | 0      | 1    | 0.4248 | 1    | 1               |
| $M_3$ | 0.4508 | 2    | 0.4160 | 2    | 2               |
| $M_4$ | 0.5384 | 3    | 0.3762 | 3    | 4               |

TABLE 13. Weights in sensitivity analysis

| WtE   | Case 1 | Case 2 | Case 3 |
|-------|--------|--------|--------|
| $M_1$ | 0.392  | 0.314  | 0.098  |
| $M_2$ | 0.196  | 0.392  | 0.314  |
| $M_3$ | 0.314  | 0.098  | 0.196  |
| $M_4$ | 0.098  | 0.196  | 0.392  |

TABLE 14. Sensitivity analysis results-Case 1

| WtE   | RA     | Rank | RP     | Rank | FMF    | Rank | DT |
|-------|--------|------|--------|------|--------|------|----|
| $M_1$ | 1.1787 | 3    | 0.0480 | 4    | 0.0559 | 2    | 2  |
| $M_2$ | 1.3402 | 1    | 0.0388 | 2    | 0.0495 | 3    | 3  |
| $M_3$ | 1.2615 | 2    | 0.0412 | 3    | 0.0396 | 4    | 4  |
| $M_4$ | 1.1424 | 4    | 0.0388 | 1    | 0.1027 | 1    | 1  |

TABLE 15. Sensitivity analysis results-Case 2

| WtE   | RA     | Rank | RP     | Rank | FMF    | Rank | DT |
|-------|--------|------|--------|------|--------|------|----|
| $M_1$ | 1.1787 | 3    | 0.0387 | 1    | 0.0401 | 4    | 4  |
| $M_2$ | 1.3402 | 1    | 0.0412 | 2    | 0.0756 | 1    | 1  |
| $M_3$ | 1.2615 | 2    | 0.0824 | 4    | 0.0744 | 2    | 2  |
| $M_4$ | 1.1424 | 4    | 0.0697 | 3    | 0.0585 | 3    | 3  |

### 6.2. Sensitivity analysis

The sensitivity analysis of this model compares the results of three cases. Case 3 is the outcome of this study, and Cases 1 and 2 are the other outcomes discovered using different weights of the criteria. Sensitivity analysis shows that modifying the weights of the criteria has an effect on the ranking order.

## 7. Conclusion

The most widely used waste-to-energy technology for residual waste uses combustion to provide combined heat and power. Adopting maximum recycling with waste-to-energy in an integrated waste management system would significantly reduce dumping in India. Waste-to-energy technologies are available that can process unsegregated low-calorific value waste, and the industries are keen to exploit these technologies in India. Several waste-to-energy projects using combustion of un-segregated low-calorific value waste are currently being developed. Alternative thermal treatment processes to combustion include gasification, pyrolysis, production of refuse derived fuel and gas-plasma technology [4]. However, these WtE technologies have some drawbacks and in order to overcome this problem and selecting the best solution for waste to energy from new trends in WtE to achieve to reduce the sustainability factors resulting from the presence of many different indicators, this paper applies a hybrid multi-criteria decision-making approach under a Pythagorean Neutrosophic fuzzy environment.

Waste to energy (WtE) technologies have been identified as a promising solution for dealing with the problem of complexly composed and ever-increasing waste volumes in developed countries such as the European Union and the United States, among others. However, governments and policymakers continue to face significant challenges in selecting appropriate WtE technologies to design sustainable waste management systems for India. As a result, this study was carried out in order to propose a general systematic framework that can assist policymakers in identifying the most appropriate WtE technologies for designing waste management systems in India. In this paper, the score function of PNFS and the PNF-MULTIMOORA method based on it have been presented. The characteristic of each WtE technology is taken in the form of PNFNs. Based on the proposed method to find the best solution for this problem, New trends in WtE have been identified as the safest and most beneficial WtE technology in the current scenario, which is obtained from the proposed method. This method contributes to waste reduction while also producing energy, which will help with future energy demand issues.

## References

1. Kahraman, C., Onar, S. ., Oztayi, B. (2016). Fuzzy decision making: Its pioneers and supportive environment. *Fuzzy Logic in Its 50th Year*, 21-58.
2. Kahraman, C., Ruan, D., Dogan, I. (2003). Fuzzy group decision-making for facility location selection. *Information sciences*, 157, 135-153.
3. <https://mnre.gov.in/waste-to-energy/current-status>.
4. Kumar, Sunil, Stephen R. Smith, Geoff Fowler, Costas Velis, S. Jyoti Kumar, Shashi Arya, Rena, Rakesh Kumar, Christopher Cheeseman. (2017). Challenges and opportunities associated with waste management in India, *Royal Society open science* 4, 3, 160764.
5. Zadeh, L. A. (1965). Fuzzy sets. *Information Control*, 8(3), 338-353.

---

R.Narmada Devi, S.Sowmiya, and A.Anuja, Selecting the Suitable Waste to Energy Technology for India Using MULTIMOORA Method under Pythagorean Neutrosophic Fuzzy Logic

6. Zadeh, L. A. (1975). The concept of a linguistic variable and its application to approximate reasoning-1, *Information sciences*, 8,199-249.
7. Slowinski, R. (Ed.). (2012). *Fuzzy sets in decision analysis, operations research and statistics* (Vol. 1). Springer Science & Business Media.
8. Atanassov, K.T. (1983). *Intuitionistic Fuzzy Sets*, VII ITKRs Session, Sofia, Deposited in Central Sci; 1697/84; Central Library of the Bulgarian Academy of Sciences: Sofia, Bulgaria.
9. Xu, Z. (2007). Intuitionistic fuzzy aggregation operators. *IEEE Transactions on Fuzzy Systems*, 15, 11791187.
10. Yager, R.R. (2013). Pythagorean fuzzy subsets. In *Proceedings of the Joint IFSAWorld Congress and NAFIPS Annual Meeting*, Edmonton, AB, Canada, June 2428, 25761.
11. Yager, R. R., Abbasov, A. M. (2013). Pythagorean membership grades, complex numbers, and decision making. *International Journal of Intelligent Systems*, 28(5), 436-452.
12. Yager, R. R. (2013). Pythagorean membership grades in multi-criteria decision making. *IEEE Transactions on Fuzzy Systems*, 22(4), 958-965.
13. Zhang, X., Xu, Z. (2014). Extension of TOPSIS to multiple criteria decision making with Pythagorean fuzzy sets. *International Journal of Intelligent Systems*, 29(12), 1061-1078.
14. Smarandache, F. (1998). *Neutrosophy/neutrosophic probability, set and logic*. American Research Press, Rehoboth.
15. Kaza, S., Yao, L., Bhada-Tata, P., Van Woerden, F. (2018). *What a waste 2.0: a global snapshot of solid waste management to 2050*. World Bank Publications.
16. DOE (2019). *Waste-to-Energy From Municipal Solids Wastes*. U.S Department of Energy. Available online at: [https://www.energy.gov/sites/prod/files/2019/08/f66/BETO-Waste-to-Energy-Report-August-752 2019.pdf](https://www.energy.gov/sites/prod/files/2019/08/f66/BETO-Waste-to-Energy-Report-August-752%2019.pdf)
17. Abdel-Basset, M., Saleh, M., Gamal, A., Smarandache, F. (2019). An approach of TOPSIS technique for developing supplier selection with group decision making under type-2 neutrosophic number. *Applied Soft Computing*, 77, 438-452.
18. Farooq, A., Haputta, P., Silalertruksa, T., Gheewala, S. H. (2021). A framework for the selection of suitable waste to energy technologies for a sustainable municipal solid waste management system. *Frontiers in Sustainability*, 2, 681690.
19. Yap, H. Y., Nixon, J. D. (2015). A multi-criteria analysis of options for energy recovery from municipal solid waste in India and the UK. *Waste management*, 46, 265-277.
20. Atwadkar, R. R., Jafhav, L. D., Wagh, M. M., Shinde, N. N. (2014). A multi criteria ranking of different technologies for the waste to energy of municipal solid waste in the city of Kolhapur. *International Journal of Emerging Technology and Advanced Engineering*, 4(7),937-942.
21. Ayodele, T. R., Ogunjuyigbe, A. S. O., Alao, M. A. (2017). Life cycle assessment of waste-to-energy (WtE) technologies for electricity generation using municipal solid waste in Nigeria. *Applied Energy*, 201, 200-218.
22. Abdel-Basset, M., Gamal, A., Chakraborty, R. K., Ryan, M. J. (2021). Evaluation approach for sustainable renewable energy systems under uncertain environment: A case study. *Renewable energy*, 168, 1073-1095.
23. Beyene, H. D., Werkneh, A. A., Ambaye, T. G. (2018). Current updates on waste to energy (WtE) technologies: a review. *Renewable Energy Focus*, 24, 1-11.
24. Chiu, H.Y., Pai, T.Y., Liu, M.H., Chang, C.A., Lo, F.C., Chang, T.C., Lo, H.M., Chiang, C.F., Chao, K.P., Lo, W.Y., Lo, S.W. (2016). Electricity production from municipal solid waste using microbial fuel cells. *Waste Management & Research*, 34(7), 619-629.
25. Abdel-Basset, M., Gamal, A., Elkomy, O. M. (2021). Hybrid Multi-Criteria Decision Making approach for the evaluation of sustainable photovoltaic farms locations. *Journal of Cleaner Production*, 328, 129526.

26. Khan, I., Kabir, Z. (2020). Waste-to-energy generation technologies and the developing economies: A multi-criteria analysis for sustainability assessment. *Renewable Energy*, 150, 320-333.
27. Kurbatova, A., Abu-Qdais, H. A. (2020). Using multi-criteria decision analysis to select waste to energy technology for a mega city: The case of Moscow. *Sustainability*, 12(23), 9828.
28. Malav, L.C., Yadav, K.K., Gupta, N., Kumar, S., Sharma, G.K., Krishnan, S., Rezaia, S., Kamyab, H., Pham, Q.B., Yadav, S., Bhattacharyya, S. (2020). A review on municipal solid waste as a renewable source for waste-to-energy project in India: Current practices, challenges, and future opportunities. *Journal of Cleaner Production*, 277, 123227.
29. Reddy, M. V. (2014). Municipal solid wastewaste to energy conversion in India: an overview. *International Journal of Environmental Technology and Management*, 17(2-4), 283-292.
30. Abdel-Basset, M., Gamal, A., Chakraborty, R. K., Ryan, M. (2021). Development of a hybrid multi-criteria decision-making approach for sustainability evaluation of bioenergy production technologies: A case study. *Journal of Cleaner Production*, 290, 125805.
31. Jansi, R., Mohana, K., Smarandache, F. (2019). Correlation measure for pythagorean neutrosophic sets with t and f as dependent neutrosophic components. *Infinite Study*.
32. Garg, H. (2017). A new improved score function of an interval-valued Pythagorean fuzzy set based TOPSIS method. *International Journal for Uncertainty Quantification*, 7(5).
33. Singh, A., Bhat, S. A. (2021). A novel score and accuracy function for neutrosophic sets and their real-world applications to multi-criteria decision-making process. *Neutrosophic Sets and Systems*, 41, 168-197.
34. Narayanamoorthy, S., Anuja, A., Kang, D., Kureethara, J. V., Kalaiselvan, S., Manirathinam, T. (2020). A Distinctive Symmetric Analyzation of Improving Air Quality Using Multi-Criteria Decision Making Method under Uncertainty Conditions. *Symmetry*, 12(11), 1858.
35. Brauers, W. K. M., Zavadskas, E. K. (2011). MULTIMOORA optimization used to decide on a bank loan to buy property. *Technological and Economic Development of Economy*, 17(1), 174-188.
36. Stanujkic, D., Zavadskas, E. K., Brauers, W. K., Karabasevic, D. (2015). An extension of the MULTIMOORA method for solving complex decision-making problems based on the use of interval-valued triangular fuzzy numbers. *Transformations in Business and Economics*, 14(2B), 355-375.
37. Brauers, W. K., Baleentis, A., Baleentis, T. (2011). MULTIMOORA for the EU Member States updated with fuzzy number theory. *Technological and Economic Development of Economy*, 17(2), 259-290.
38. Kersulienė, V., Zavadskas, E. K., Turskis, Z. (2010). Selection of rational dispute resolution method by applying new stepwise weight assessment ratio analysis (SWARA). *Journal of Business Economics and Management*, 11(2), 243-258.
39. Radhika, S., Kumar, D. S., Swapna, D. (2013). VIKOR method for multi criteria decision making in academic staff selection. *Journal of Production research and Management*, 3(2), 30-35.
40. Perez-Domnguez, L., Mojica, K. S., Pabon, L. O., Daz, M. C. (2018). Application of the MOORA method for the evaluation of the industrial maintenance system. In *Journal of Physics: Conference Series*, 1126, 1, 012018. IOP Publishing.

Received: April 6, 2023. Accepted: July 18, 2023